

Kawasaki

Let the Good Times Roll®



KLX

2025

Product Spec Book

2025

KLX[®]110R



MSRP
\$2,899

 LIME GREEN

 BATTLE GRAY



POWER		Front Tire	
Engine	4-stroke, single-cylinder, SOHC, air-cooled	2.50 x 14	
Displacement	112cc	Rear Tire	
Bore x Stroke	53.0 x 50.6mm	3.00 x 12	
Compression Ratio	9.5:1	Front Brakes	
Fuel System	Keihin PB18 carburetor and screw type throttle limiter on grip housing	90mm mechanical drum, cable actuated	
Ignition	DC-CDI	Rear Brakes	
Transmission	4-speed, return shift, automatic centrifugal and wet, multi-disc clutch	110mm mechanical drum, rod actuated	
Final Drive	Chain	DETAILS	
PERFORMANCE		Frame Type	Backbone frame, high-tensile steel
Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/4.3 in	Rake/Trail	24.8° /2.0 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/4.3 in	Overall Length	61.4 in
		Overall Width	25.6 in
		Overall Height	37.6 in
		Ground Clearance	8.5 in
		Seat Height	26.8 in
		Curb Weight	167.5 lb*
		Fuel Capacity	1.0 gal
		Wheelbase	42.3 in
		Color Choices	Lime Green, Battle Gray

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX®110R L

Kawasaki
Let the Good Times Roll®



MSRP
\$3,099

 LIME GREEN

 BATTLE GRAY



POWER

Engine	4-stroke, single-cylinder, SOHC, air-cooled
Displacement	112cc
Bore x Stroke	53.0 x 50.6mm
Compression Ratio	9.5:1
Fuel System	Keihin PB18 carburetor and screw type throttle limiter on grip housing
Ignition	DC-CDI
Transmission	4-speed, return shift, wet multi-disc manual clutch
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	30mm hydraulic telescopic fork/5.5 in
Rear Suspension / Wheel Travel	Swingarm with single hydraulic shock/5.2 in

Front Tire	2.50 x 14
Rear Tire	3.00 x 12
Front Brakes	90mm mechanical drum, cable actuated
Rear Brakes	110mm mechanical drum, rod actuated

DETAILS

Frame Type	Backbone frame, high-tensile steel
Rake/Trail	24.2° / 1.9 in
Overall Length	61.4 in
Overall Width	25.6 in
Overall Height	39.0 in
Ground Clearance	10.4 in
Seat Height	28.7 in
Curb Weight	167.5 lb*
Fuel Capacity	1.0 gal
Wheelbase	42.3 in
Color Choices	Lime Green, Battle Gray

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX®140R

Kawasaki
Let the Good Times Roll®



MSRP
\$3,699

-  LIME GREEN
-  BATTLE GRAY



POWER		Rear Tire	
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Front Brakes	90/100-14
Displacement	144cc	Rear Brakes	Single 220mm petal disc with a dual-piston caliper
Bore x Stroke	58.0 x 54.4mm		Single 186mm petal disc with single-piston caliper
Compression Ratio	9.5:1	DETAILS	
Fuel System	Keihin PB20 carburetor	Frame Type	High-tensile steel, box-section perimeter
Ignition	Digital DC-CDI	Rake/Trail	27.0° / 3.3 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Length	71.7 in
Final Drive	Chain	Overall Width	31.1 in
PERFORMANCE		Overall Height	41.3 in
Front Suspension / Wheel Travel	33mm telescopic fork/7.1 in	Ground Clearance	9.3 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with 5-way preload adjustability/7.1 in	Seat Height	30.7 in
Front Tire	70/100-17	Curb Weight	205.0 lb*
		Fuel Capacity	1.5 gal
		Wheelbase	49.6 in
		Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX[®]140R F



MSRP
\$4,299

 LIME GREEN

 BATTLE GRAY



POWER		Front Tire	
Engine	4-stroke, single-cylinder, SOHC, air-cooled	2.75 x 21	
Displacement	144cc	Rear Tire	
Bore x Stroke	58.0 x 54.4mm	4.10 x 18	
Compression Ratio	9.5:1	Front Brakes	
Fuel System	Keihin PB20 carburetor	Single 220mm petal disc with a dual-piston caliper	
Ignition	Digital DC-CDI	Rear Brakes	
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Single 186mm petal disc with single-piston caliper	
Final Drive	Chain	DETAILS	
PERFORMANCE		Frame Type	High-tensile steel, box-section perimeter
Front Suspension / Wheel Travel	33mm telescopic fork/7.5 in	Rake/Trail	27.0° /4.6 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with piggyback reservoir, 20-way rebound damping and threaded preload adjustability/7.9 in	Overall Length	78.9 in
		Overall Width	31.1 in
		Overall Height	44.7 in
		Ground Clearance	12.4 in
		Seat Height	33.9 in
		Curb Weight	218.2 lb*
		Fuel Capacity	1.5 gal
		Wheelbase	52.4 in
		Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX®140R L

Kawasaki
Let the Good Times Roll®



MSRP
\$3,999

 LIME GREEN

 BATTLE GRAY



POWER		Front Tire	70/100-19
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Rear Tire	90/100-16
Displacement	144cc	Front Brakes	Single 220mm petal disc with a dual-piston caliper
Bore x Stroke	58.0 x 54.4mm	Rear Brakes	Single 186mm petal disc with single-piston caliper
Compression Ratio	9.5:1	DETAILS	
Fuel System	Keihin PB20 carburetor	Frame Type	High-tensile steel, box-section perimeter
Ignition	Digital DC-CDI	Rake/Trail	27.0° / 3.8 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Length	74.6 in
Final Drive	Chain	Overall Width	31.1 in
PERFORMANCE		Overall Height	42.3 in
Front Suspension / Wheel Travel	33mm telescopic fork/7.1 in	Ground Clearance	10.0 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in	Seat Height	31.5 in
		Curb Weight	209.4 lb*
		Fuel Capacity	1.5 gal
		Wheelbase	50.6 in
		Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX® 230R

Kawasaki
Let the Good Times Roll®



MSRP
\$4,999

 LIME GREEN

 BATTLE GRAY



POWER		Rear Tire	
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Front Brakes	100/100-18
Displacement	233cc	Rear Brakes	Single 240mm petal disc with a dual-piston caliper
Bore x Stroke	67.0 x 66.0mm		Single 220mm petal disc with single-piston caliper
Compression Ratio	9.4:1	DETAILS	
Fuel System	DFI® with 32mm Keihin throttle body	Frame Type	High-tensile steel, box-section perimeter
Ignition	TCBI with electronic advance	Rake/Trail	25.4° / 4.2 in
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Length	80.5 in
Final Drive	Chain	Overall Width	33.3 in
PERFORMANCE		Overall Height	47.2 in
Front Suspension / Wheel Travel	37mm telescopic fork/9.8 in	Ground Clearance	11.4 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/9.8 in	Seat Height	35.6 in
Front Tire	80/100-21	Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
		Fuel Capacity	2.0 gal
		Wheelbase	54.1 in
		Color Choices	Lime Green, Battle Gray

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX® 230R S



MSRP
\$4,999

 LIME GREEN

 BATTLE GRAY



POWER	
Engine	4-stroke, single-cylinder, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Fuel System	DFI® with 32mm Keihin throttle body
Ignition	TCBI with electronic advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	100/100-18
Front Brakes	Single 240mm petal disc with a dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

PERFORMANCE	
Front Suspension / Wheel Travel	37mm telescopic fork/8.7 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	80/100-21

DETAILS	
Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	24.6° / 3.9 in
Overall Length	80.5 in
Overall Width	33.3 in
Overall Height	46.7 in
Ground Clearance	10.6 in
Seat Height	34.4 in
Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.3 in
Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX® 230 S



MSRP NON-ABS
\$4,999

MSRP ABS
\$5,299



LIME GREEN



POWER	
Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Torque	13.0 lb-ft @ 6,400 rpm
Fuel System	DFI® with 32mm throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

PERFORMANCE	
Front Suspension / Wheel Travel	37mm telescopic fork/7.9 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

Front Brakes	Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)
Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)

DETAILS	
Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.6° / 3.8 in
Overall Length	81.9 in
Overall Width	33.3 in
Overall Height	44.9 in
Ground Clearance	9.4 in
Seat Height	33.3 in
Estimated Dry Weight	275.6 lb** (ABS), 273.4 lb** (non-ABS) / 277.7 lb** (ABS), 275.5 lb** (non-ABS) 50-State Model
Curb Weight	291.1 lb* (ABS), 288.9 lb* (non-ABS) / 293.3 lb* (ABS), 291.1 lb* (non-ABS) 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT®, LCD Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP MOTORCYCLE
Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX®230SM ABS

Kawasaki

Let the Good Times Roll®



MSRP

\$5,599

 BATTLE GRAY



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Torque	13.0 lb-ft @ 6,400 rpm
Fuel System	DFI® with 32mm throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

Rear Tire	120/70-17
Front Brakes	Single 300mm petal disc with a dual-piston caliper and ABS
Rear Brakes	Single 220mm petal disc with single-piston caliper and ABS

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Trail	24.9°/3.0 in
Overall Length	80.1 in
Overall Width	33.3 in
Overall Height	44.3 in
Ground Clearance	8.7 in
Seat Height	33.1 in
Estimated Dry Weight	284.4/286.5 lb** 50-State Model
Curb Weight	299.9/302.1 lb* 50-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT®, LCD Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP MOTORCYCLE
Color Choices	Battle Gray

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.4 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	110/70-17

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

2025

KLX[®]300

Kawasaki
Let the Good Times Roll[®]



MSRP
\$5,449

 LIME GREEN

 BATTLE GRAY



POWER		Front Tire	3.0 x 21
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled	Rear Tire	4.6 x 18
Displacement	292cc	Front Brakes	Single 250mm petal disc with a dual-piston caliper
Bore x Stroke	78.0 x 61.2mm	Rear Brakes	Single 240mm petal disc with single-piston caliper
Compression Ratio	11.1:1	DETAILS	
Maximum Torque	18.1 lb-ft @ 7,000 rpm	Frame Type	Tubular, semi-double cradle
Fuel System	DFI [®] with 34mm Keihin throttle body	Rake/Trail	26.7° / 4.2 in
Ignition	CDI	Overall Length	86.6 in
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Width	32.3 in
Final Drive	Chain	Overall Height	47.4 in
PERFORMANCE		Ground Clearance	10.8 in
Front Suspension / Wheel Travel	43mm inverted telescopic fork with adjustable compression damping/10.0 in	Seat Height	35.2 in
Rear Suspension / Wheel Travel	Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/9.1 in	Curb Weight	302.1 lb*
		Fuel Capacity	2.1 gal
		Wheelbase	56.7 in
		Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

KLX®300R



MSRP
\$5,549

 LIME GREEN

 BATTLE GRAY



POWER		Front Tire	
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled	Rear Tire	3.0 x 21
Displacement	292cc	Front Brakes	4.6 x 18
Bore x Stroke	78.0 x 61.2mm	Rear Brakes	Single 270mm petal disc with a dual-piston caliper
Compression Ratio	11.0:1		Single 240mm petal disc with single-piston caliper
Fuel System	DFI® with 34mm Keihin throttle body	DETAILS	
Ignition	TCBI with electronic advance	Frame Type	Semi-double cradle
Transmission	6-speed, return shift with wet multi-disc manual clutch	Rake/Trail	26.9° / 4.3 in
Final Drive	Chain	Overall Length	86.6 in
		Overall Width	32.5 in
		Overall Height	49.0 in
		Ground Clearance	11.8 in
		Seat Height	35.4 in
		Curb Weight	282.2 lb* / 286.7 lb* 50-State Model
		Fuel Capacity	2.1 gal
		Wheelbase	56.5 in
		Color Choices	Lime Green, Battle Gray
PERFORMANCE			
Front Suspension / Wheel Travel	43mm inverted telescopic fork with adjustable compression damping/11.2 in		
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/11.2 in		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.

2025

KLX®300SM

Kawasaki
Let the Good Times Roll®



MSRP
\$5,849

-  BATTLE GRAY
-  PHANTOM BLUE



POWER	
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled
Displacement	292cc
Bore x Stroke	78.0 x 61.2mm
Compression Ratio	11.1:1
Maximum Torque	18.1 lb-ft @ 7,000 rpm
Fuel System	DFI® with 34mm Keihin throttle body
Ignition	CDI
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/8.1 in
Front Tire	110/70-17
Rear Tire	130/70-17
Front Brakes	Single 300mm petal disc with a dual-piston caliper
Rear Brakes	Single 240mm petal disc with single-piston caliper

PERFORMANCE	
Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping/9.1 in

DETAILS	
Frame Type	Tubular, semi-double cradle
Rake/Trail	25.0°/2.8 in
Overall Length	83.3 in
Overall Width	31.1 in
Overall Height	44.7 in
Ground Clearance	9.3 in
Seat Height	33.9 in
Curb Weight	304.3 lb*
Fuel Capacity	2.1 gal
Wheelbase	56.5 in
Color Choices	Battle Gray, Phantom Blue

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.