

Kawasaki

Let the Good Times Roll®



KX

2025

Product Spec Book

2025
KX™ 65



MSRP
\$4,249

 LIME GREEN



POWER		Rear Tire	
Engine	2-stroke, single-cylinder, liquid-cooled	Front Brakes	80/100-12
Displacement	64cc	Rear Brakes	Single 180mm disc with single-piston caliper
Bore x Stroke	44.5 x 41.6mm	DETAILS	
Compression Ratio	8.4:1	Frame Type	High-tensile steel semi-double cradle
Fuel System	24mm Mikuni carburetor	Rake/Trail	27.0° / 2.4 in
Ignition	CDI with digital advance	Overall Length	62.6 in
Transmission	6-speed, return shift, with wet multi-disc manual clutch	Overall Width	29.9 in
Final Drive	Chain	Overall Height	37.6 in
PERFORMANCE		Ground Clearance	12.0 in
Front Suspension / Wheel Travel	33mm leading axle telescopic fork with 4-way rebound damping/8.3 in	Seat Height	29.9 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in	Curb Weight	132.2 lb*
Front Tire	60/100-14	Fuel Capacity	1.0 gal
		Wheelbase	44.1 in
		Color Choices	Lime Green

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025
KX™ 85



MSRP
\$4,949

 LIME GREEN



POWER	
Engine	2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled
Displacement	84cc
Bore x Stroke	48.5 x 45.8mm
Compression Ratio	10.9:1 (low speed) / 9.0:1 (high speed)
Fuel System	28mm Keihin carburetor
Ignition	CDI with digital advance
Transmission	6-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	90/100-14
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 184mm petal disc with single-piston caliper

PERFORMANCE	
Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in
Front Tire	70/100-17

DETAILS	
Frame Type	High-tensile steel perimeter design with subframe member
Rake/Trail	29.0°/3.8 in
Overall Length	72.0 in
Overall Width	30.1 in
Overall Height	43.3 in
Ground Clearance	11.4 in
Seat Height	32.7 in
Curb Weight	164.4 lb*
Fuel Capacity	1.32 gal
Wheelbase	49.8 in
Special Features	ERGO-FIT®
Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

2025
KX™112

Kawasaki
Let the Good Times Roll®



MSRP
\$5,649

 LIME GREEN



POWER			
Engine	2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled	Rear Tire	90/100-16
Displacement	112cc	Front Brakes	Single 220mm petal disc with dual-piston caliper
Bore x Stroke	52.5 x 51.6mm	Rear Brakes	Single 184mm petal disc with single-piston caliper
Compression Ratio	9.9:1 (low speed) / 8.6:1 (high speed)	DETAILS	
Fuel System	28mm Keihin carburetor	Frame Type	High-tensile steel perimeter design with subframe member
Ignition	CDI with digital advance	Rake/Trail	29.0° / 4.3 in
Transmission	6-speed, return shift, with wet multi-disc manual clutch	Overall Length	75.6 in
Final Drive	Chain	Overall Width	30.1 in
PERFORMANCE		Overall Height	45.3 in
Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in	Ground Clearance	13.0 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in	Seat Height	34.3 in
Front Tire	70/100-19	Curb Weight	169.7 lb*
		Fuel Capacity	1.32 gal
		Wheelbase	51.6 in
		Special Features	ERGO-FIT®
		Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

2025

KX™ 250



MSRP

\$8,999

 LIME GREEN



POWER	
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.0:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain
Electronic Rider Aids	Power Modes, Kawasaki Traction Control (KTRC), Launch Control Mode

Front Tire	80/100-21
Rear Tire	110/90-19
Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking petal disc with single-piston caliper

PERFORMANCE	
Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 23-way compression damping and 20-way rebound damping /12.0 in
Rear Suspension / Wheel Travel	Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.1 in

DETAILS	
Frame Type	Aluminum perimeter
Rake/Trail	27.0° /4.7 in
Overall Length	86.2 in
Overall Width	32.3 in
Overall Height	49.8 in
Ground Clearance	13.4 in
Seat Height	37.6 in
Curb Weight	230.8 lb* without fuel / 240.7 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Special Features	Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®
Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

2025

KX™ 250X



MSRP
\$9,099

 LIME GREEN



POWER	
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.0:2
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain
Electronic Rider Aids	Power Modes, Kawasaki Traction Control (KTRC), Launch Control Mode

Front Tire	80/100-21
Rear Tire	110/100-18
Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking petal disc with single-piston caliper

PERFORMANCE	
Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 23-way compression damping and 20-way rebound damping /12.0 in
Rear Suspension / Wheel Travel	Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.1 in

DETAILS	
Frame Type	Aluminum perimeter
Rake/Trail	27.5° /4.8 in
Overall Length	85.8 in
Overall Width	32.3 in
Overall Height	49.6 in
Ground Clearance	13.0 in
Seat Height	37.2 in
Curb Weight	233.2 lb* without fuel / 243.2 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Special Features	Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®
Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

2025
KX™ 450

Kawasaki
Let the Good Times Roll®



MSRP
\$10,499

 LIME GREEN



POWER	
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled
Displacement	449cc
Bore x Stroke	96.0 x 62.1mm
Compression Ratio	12.5:1
Fuel System	DFI® with 44mm Keihin throttle body
Ignition	Digital CDI with handlebar-controlled power modes
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain
Electronic Rider Aids	Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode
PERFORMANCE	
Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 21-way adjustable compression and 22-way adjustable rebound damping/12.0 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in

Front Tire	80/100-21
Rear Tire	120/80-19
Front Brakes	Single semi-floating 270mm Braking/Sunstar petal disc with Brembo master cylinder and dual-piston caliper
Rear Brakes	Single 240mm Braking/Sunstar petal disc with single-piston caliper

DETAILS	
Frame Type	Aluminum perimeter
Rake/Trail	26.6° / 4.5 in
Overall Length	85.8 in
Overall Width	32.3 in
Overall Height	50.0 in
Ground Clearance	13.6 in
Seat Height	37.8 in
Curb Weight	238.3 lb* without fuel / 248.2 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.3 in
Special Features	Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®
Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.

2025

KX™ 450SR

Kawasaki
Let the Good Times Roll®



MSRP
\$13,599

 LIME GREEN



POWER		Front Tire	
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled	80/100-21	
Displacement	449cc	Rear Tire	
Bore x Stroke	96.0 x 62.1mm	120/80-19	
Compression Ratio	12.5:1	Front Brakes	
Fuel System	DFI® with 44mm Keihin throttle body	Single semi-floating 270mm Braking/Sunstar petal disc with Brembo master cylinder and dual-piston caliper	
Ignition	Digital CDI with handlebar-controlled power modes	Rear Brakes	
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation	Single 240mm Braking/Sunstar petal disc with single-piston caliper	
Final Drive	Chain	DETAILS	
Electronic Rider Aids	Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode	Frame Type	Aluminum perimeter
PERFORMANCE		Rake/Trail	26.6° / 4.5 in
Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 21-way adjustable compression and 22-way adjustable rebound damping/12.0 in	Overall Length	86.0 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in	Overall Width	32.3 in
		Overall Height	50.0 in
		Ground Clearance	13.4 in
		Seat Height	37.6 in
		Curb Weight	238.2 lb* without fuel / 248.2 lb*
		Fuel Capacity	1.64 gal
		Wheelbase	58.5 in
		Special Features	Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®
		Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025
KX™ 450X



MSRP
\$10,699

 LIME GREEN



POWER		Front Tire	
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled	80/100-21	
Displacement	449cc	Rear Tire	
Bore x Stroke	96.0 x 62.1mm	120/80-18	
Compression Ratio	12.5:1	Front Brakes	
Fuel System	DFI® with 44mm Keihin throttle body	Single semi-floating 270mm Braking/Sunstar petal disc with Brembo master cylinder and dual-piston caliper	
Ignition	Digital CDI with handlebar-controlled power modes	Rear Brakes	
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation	Single 240mm Braking/Sunstar petal disc with single-piston caliper	
Final Drive	Chain	DETAILS	
Electronic Rider Aids	Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode	Frame Type	Aluminum perimeter
PERFORMANCE		Rake/Trail	27.0° / 4.6 in
Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 21-way adjustable compression and 22-way adjustable rebound damping/12.0 in	Overall Length	85.6 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in	Overall Width	32.1 in
		Overall Height	49.6 in
		Ground Clearance	13.2 in
		Seat Height	37.4 in
		Curb Weight	239.8 lb* without fuel / 249.9 lb*
		Fuel Capacity	1.64 gal
		Wheelbase	58.3 in
		Special Features	Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®
		Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.