Kawasaki

Let the Good Times Roll®



MULE[™] 4000





MSRP \$10,899



TIMBERLINE GREEN



POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

617cc **Displacement**

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

DFI® with 34mm Mikuni throttle body **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Nο

Alternator Output

23 amp

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.9 in

Rear Suspension /

DeDion Axle/2.8 in

Wheel Travel

Front Tires

Front Brakes

23 x 11-10

Rear Tires 23 x 11-10

Steering Rack-and-pinion

Drum

Rear Brakes Drum **Park Brake Type** Independent, mechanical drum

Ground Clearance 7.5 in

Fuel Capacity 6.3 gal

Turning Radius 11.0 ft

Cargo Bed Dimensions 46.3 x 51.6 x 11.4 in

(LxWxH)

Cargo Bed Load 800 lb

Capacity

Payload Capacity 1,327 lb

Seating Capacity

Towing Capacity

1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

DETAILS

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 75.8 in

Estimated Dry

Weight

1,272.3 lb**

Curb Weight

1,338.4 lb*

Wheelbase

73.6 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green

Scan with camera to view videos. key features



MULE 4000 TRANS™





\$12,099



BRIGHT WHITE



Independent, mechanical drum

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

617cc **Displacement**

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Nο

Alternator Output

23 amp

Turni
Cargo Dime (LxW
Cargo Capa

6.3 gal

ing Radius 12.8 ft

7.7 in

50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4o Bed ensions xH)

800 lb (2-person) / 401 lb (4-person)

o Bed Load city

Park Brake Type

Ground Clearance

Fuel Capacity

Payload Capacity 1,330 lb

Seating Capacity 2-4

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.9 in

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23 x 11-10 **Rear Tires** 23 x 11-10

Steering Rack-and-pinion

Front Brakes Drum **Rear Brakes** Drum **Estimated Dry** Weight

Curb Weight

DETAILS

Overall Length

Overall Width

Overall Height

1,448.7 lb**

128.5 in

58.5 in

75.8 in

1,514.8 lb* Wheelbase 85.2 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Bright White

Scan with camera to view videos. key features



MULE[™] 4010 4x4





\$12,199



TIMBERLINE GREEN



DARK ROYAL RED



POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

617cc **Displacement**

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

23 amp

Nο

Park Brake Type	Independent, mechanical drum

Ground Clearance 6.9 in

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed Dimensions 46.3 x 51.6 x 11.4 in

(LxWxH)

Cargo Bed Load 800 lb

Capacity

1,327 lb

Seating Capacity

Towing Capacity

Payload Capacity

1,200 lb

Lighting

(2) Halogen headlights, (2) tail/brake lights

CAPABILITY

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel**

Rear Suspension /

DeDion Axle/2.8 in

Wheel Travel

Front Tires

23 x 11-10

Rear Tires 23 x 11-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes Drum **Rear Brakes** Drum

DETAILS

Overall Length 116.7 in **Overall Width** 62.0 in

Overall Height 75.8 in

Estimated Dry

Weight

1,367.1 lb**

Curb Weight

1,433.3 lb*

Wheelbase

73.6 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Scan with camera to view videos. key features



MULE[™] 4010 4x4 FE





\$12,399



BRIGHT WHITE



POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

617cc **Displacement**

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System

23 amp

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

DFI® with 34mm Mikuni throttle body

Nο

Alternator Output

Park Brake Type Independent, mechanical drum

Ground Clearance 6.9 in

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed Dimensions 46.3 x 51.6 x 11.4 in

(LxWxH)

800 lb

Capacity

Cargo Bed Load

DETAILS

Payload Capacity 1,312 lb

Seating Capacity

Towing Capacity

1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.9 in

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires

23 x 11-10

Rear Tires 23 x 11-10

Steering

Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes

Drum

Rear Brakes Drum

Overall Length 116.7 in

Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb*

Wheelbase 73.6 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Scan with camera to view videos. key features and more.



MULE™ 4010 TRANS4x4®





\$13,549

TIMBERLINE GREEN



DARK ROYAL RED



POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

617cc **Displacement**

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

23 amp

Nο

Park Brake Type	Independent, mechanical drum
Ground Clearance	7.1 in
Fuel Capacity	6.3 gal
Turning Radius	12.8 ft
Cargo Bed Dimensions (LxWxH)	50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-person)
Cargo Bed Load Capacity	800 lb (2-person) / 401 lb (4-person)
Payload Capacity	1,330 lb
Seating Capacity	2-4
Towing Capacity	1,200 lb

(2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.9 in

Rear Suspension /

DeDion Axle/2.8 in

Wheel Travel

Front Tires

23 x 11-10

Rear Tires 23 x 11-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes Drum

Rear Brakes Drum

DETAILS

Lighting

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 75.8 in

Estimated Dry

Weight

1,521.5 lb**

Curb Weight

1,587.6 lb*

Wheelbase

85.2 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices

Timberline Green, Dark Royal Red

Scan with camera to view videos. key features



MULE PRO-DX™ EPS





\$17,999



BRIGHT WHITE



POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

74.0 x 77.0mm **Bore x Stroke**

Compression Ratio 23.5:1

Bosch in-line injection pump **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 55 amp

(max)

Ground Clearance 10.4 in

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Fuel Capacity

Capacity

Payload Capacity 1,574 lb

Seating Capacity 3-person

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

7.9 gal

999 lb

54.1 x 53.7 x 11.0 in

CAPABILITY

Front Suspension / Double wishbone/8.7 in **Wheel Travel**

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12

Rear Tires 26 x 11-12

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual disc, 2-piston caliper Dual disc, 1-piston caliper **Rear Brakes**

Park Brake Type Independent, mechanical disc

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in

Overall Height 77.4 in

Estimated Dry 1,781.6 lb** Weight

Curb Weight 1,858.8 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

> 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Color Choices

Scan with camera to view videos. key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied) All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

MULE PRO-DXT™ EPS





\$19,799



SUPER BLACK



POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement

38.3 lb-ft @ 2,400 rpm **Maximum Torque**

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Bosch in-line injection pump **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking Yes

Alternator Output

(max)

55 amp

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Rear Tires

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12

Electric Power Steering (EPS), Tilt steering Steering **Front Brakes** Dual disc, 2-piston caliper

26 x 11-12

Dual disc, 1-piston caliper **Rear Brakes**

Independent, mechanical disc **Park Brake Type**

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Dimensions (LxWxH)**

999 lb (3-person) / 350 lb (6-person)

Cargo Bed Load Capacity

Payload Capacity 1,574 lb

3-person (1-row), 6-person (2-row) **Seating Capacity**

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

DETAILS

133.3 in **Overall Length**

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1.942.6 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Color Choices Super Black





MULE PRO-DXT™ FE EPS





\$19,999



BRIGHT WHITE



POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement

38.3 lb-ft @ 2,400 rpm **Maximum Torque**

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Bosch in-line injection pump **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking Yes

Alternator Output

(max)

55 amp

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12 **Rear Tires** 26 x 11-12

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual disc, 2-piston caliper Dual disc, 1-piston caliper **Rear Brakes** Independent, mechanical disc **Park Brake Type**

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load Capacity

Payload Capacity

3-person (1-row), 6-person (2-row) **Seating Capacity**

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

79.5 in

1,574 lb

DETAILS

Overall Height

133.3 in **Overall Length**

Overall Width 64.0 in

1.971.3 lb* **Curb Weight**

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person) / 350 lb (6-person)

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

MULE PRO-FX™ 1000 HD EDITION





\$16,799



FIRECRACKER RED



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10 1.1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

90 amp

(max) **CAPABILITY**

Front Suspension / **Wheel Travel**

Double wishbone/11.0 in

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires 26 x 9-12, radial

26 x 11-12, radial

Rear Tires Wheel Type

Steel

Steering

Rack-and-pinion

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Park Brake Type

Independent, mechanical disc

Ground Clearance 11.9 in (max), 11.8 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16 0 ft

Cargo Bed

Dimensions (LxWxH)

999/600 lb CA Model

54.1 x 53.3 x 11.0 in

Cargo Bed Load

Capacity

Payload Capacity

1.616.3/1.263.5 lb CA Model

3

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

DETAILS

Overall Length 136.6 in **Overall Width** 64.0 in **Overall Height** 811 in

Estimated Dry Weight 1,816.9/1,819.1 lb** CA Model

Curb Weight 1,891.9/1,894.1 lb* CA Model

Wheelbase

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Additional Features Roof, Rear Bumper, Additional Under Seat Storage Bin,

Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear Suspension, Anti-cinch Seatbelts

Color Choices Firecracker Red

Scan with camera to view videos. key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE[™] PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

MULE PRO-FXR™ 1000





MSRP **\$15,099**



METALLIC SIERRA BLUE



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 90 amp

(max)

Park Brake Type Independent, mechanical disc

Ground Clearance 13.2 in (max), 12.2 in (std)

Fuel Capacity 7.9 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

999/600 lb CA Model

37.6 x 53.3 x 11.0 in

Payload Capacity 1,616.3/1,263.5 lb CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Wheel Travel Double wishbone/11.0 in

Rear Suspension / Wheel Travel Double wishbone/10.1 in

Front Tires

27 x 9-12, radial

Rear Tires

27 x 11-12, radial

Wheel Type

Alloy

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

DETAILS

Overall Length 122.0 in

Overall Width 64.0 in

Overall Height 77.2 in

Estimated Dry Weight 1,660.4/1,662.6 lb** CA Model

Curb Weight 1,735.3/1,737.5 lb* CA Model

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Additional Features Rear Bumper, Contoured Two-Tone Bench Seat

Metallic Sierra Blue

Scan with camera to view videos, key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULETM PRO Series side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the

Color Choices

MULE PRO-FXR™ 1000 LE





MSRP **\$16,199**



ICE GRAY



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output

(max)

90 amp

Park Brake Type Independent, mechanical disc

Ground Clearance 13.2 in (max), 12.2 in (std)

Fuel Capacity 7.9 gal
Turning Radius 14.0 ft

Cargo Bed 37.6 x 53.3 x 11.0 in

Dimensions (LxWxH)

Cargo Bed Load

Capacity

999/600 lb CA Model

Payload Capacity 1,616.3/1,263.5 lb CA Model

Seating Capacity

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/11.0 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires 27 x 9-12, radial

Rear Tires 27 x 11-12, radial

Wheel Type Allo

Steering Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

DETAILS

Overall Length 122.0 in

Overall Height 78.5 in

Overall Height 78.5 in

Estimated Dry Weight 1,671.4/1,673.6 lb** CA Model

Curb Weight 1,746.4/1,748.6 lb* CA Model

Wheelbase 79.7 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Additional Features Roof, R

Roof, Rear Bumper, Contoured Two-Tone Bench Seat,

Additional Cup Holders

Color Choices Ice Gray

Scan with camera to view videos, key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the process of the product warnings always wear protective gear appropriate for the use of this vehicle. Never operate under the product warnings always wear protective gear appropriate for the use of this vehicle.

MULE PRO-FXT™ 1000 LE





\$18,799



CANDY PERSIMMON RED



ICE GRAY



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10 1.1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 90 amp

(max)

Park Brake Type Independent, mechanical disc

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius

Cargo Bed

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-Dimensions (LxWxH)

Cargo Bed Load Capacity

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

Payload Capacity 1,616.3/1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/11.0 in

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires

26 x 9-12, radial

Rear Tires

26 x 11-12, radial

Wheel Type

Alloy

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

DETAILS

Overall Length 135.8 in

Overall Width 64 0 in

Overall Height 80.9 in

Estimated Dry Weight 1,839.0/1,841.2 lb** CA Model

Curb Weight 1,913.9/1,916.1 lb* CA Model

Wheelhase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Additional Features Roof, Additional Front Cup Holders

Color Choices Candy Persimmon Red, Ice Gray

Scan with camera to view videos. key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE[™] PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

MULE PRO-FXT™ 1000 LE CAMO





\$18,899



TRUETIMBER® STRATA



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10 1.1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

(max)

90 amp

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/11.0 in

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires

26 x 9-12, radial

Rear Tires

26 x 11-12, radial

Wheel Type

Alloy

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Park Brake Type Independent, mechanical disc

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius

Cargo Bed

Dimensions (LxWxH)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Cargo Bed Load

Payload Capacity

Capacity

1,616.3/1,263.5 lb CA Model

Seating Capacity

3-person (1 row), 6 person (2 row)

Towing Capacity

Lighting (2) Halogen headlights, (2) LED headlights

DETAILS

Overall Length 135.8 in

Overall Width 64 0 in

Overall Height 80.9 in

Estimated Dry Weight 1,847.8/1,850.0 lb** CA Model

Curb Weight 1,922.8/1,925.0 lb* CA Model

Wheelhase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Additional Features Roof, Additional Front Cup Holders

TRUETIMBER® STRATA **Color Choices**

Scan with camera to view videos. key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE[™] PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

MULE PRO-FXT™ 1000 LE RANCH EDITION





\$20,399



METALLIC DEEP RED



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

DFI® with 38mm throttle body **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive**

differential lock

Engine Braking

Alternator Output

(max)

90 amp

Park Brake Type Independent, mechanical disc **Ground Clearance** 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

Dimensions (LxWxH)

Cargo Bed Load

Payload Capacity

Capacity

1,616.3/1,263.5 lb CA Model

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/11.0 in

Rear Suspension /

Double wishbone/10.1 in

Wheel Travel Front Tires

Rear Tires

26 x 9-12, radial 26 x 11-12, radial

Wheel Type

Allov

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

DETAILS

Overall Length 135.8 in

Overall Width 64.0 in

Overall Height

Estimated Dry Weight 1,891.9/1,894.1 lb** CA Model

Curb Weight

1.966.9/1.969.1 lb* CA Model

Wheelbase

92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Additional Features

Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Self-Leveling Rear Suspension

Color Choices Metallic Deep Red

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION





\$21,899



METALLIC STARDUST WHITE



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

92.0 x 75.1mm Bore x Stroke

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Double wishbone/11.0 in

Double wishbone/10.1 in

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output

(max)

90 amp

CAPABILITY

Front Suspension /

Wheel Travel

Rear Suspension /

Wheel Travel

26 x 9-12, radial **Front Tires Rear Tires** 26 x 11-12, radial

Wheel Type Alloy

Steering Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering

Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

Park Brake Type Independent, mechanical disc

Ground Clearance 12.6 in (max), 11.6 in (std) **Fuel Capacity Turning Radius**

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

1,616.3/1,263.5 lb CA Model

3-person (1 row), 6 person (2 row)

2,000 lb

(4) LED headlights

DETAILS

Overall Length 140.2 in **Overall Width** 64.0 in **Overall Height** 80.9 in

Estimated Dry Weight 1,955.8/1,958.0 lb** CA Model

Curb Weight 2,030.8/2,033.0 lb* CA Model

Wheelbase

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Additional Features

Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror, Additional Under Seat Storage Bin

Color Choices Metallic Stardust White

Scan with camera to view videos. key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

MULE PRO-MX™ EPS





MSRP **\$14,099**



GRAY



TIMBERLINE GREEN



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 3

(max)

35.7 amp

Park Brake Type Independent, mechanical disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed Dimensions (LxWxH) 33.4 x 44.1 x 9.1 in

Cargo Bed Load Capacity 699 lb / 600 lb CA Model

Payload Capacity

1,200 lb / 1,100 lb CA Model

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

Front Tires 25 x 8-12, radial

Rear Tires 25 x 10-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

DETAILS

Overall Length 110.0 in
Overall Width 60.0 in

Overall Height 74.4 in

Curb Weight 1,587.6 lb* / 1,589.8 lb* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator

lamp, seatbelt reminder lamps

Color Choices Gray, Timberline Green





MULE PRO-MX™ LE





MSRP **\$14,699**



DEEP BLUE



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695c

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Ground Clearance	10.6 in
Fuel Capacity	9.5 gal
Turning Radius	14.0 ft
Cargo Bed Dimensions (LxWxH)	33.4 x 44.1 x 9.1 in
Cargo Bed Load Capacity	699 lb / 600 lb CA Model
Payload Capacity	1,200 lb / 1,100 lb CA Model
Seating Capacity	2
Towing Capacity	1,500 lb
Lighting	(2) Halogen headlights, (2) LED headlights

Independent, mechanical disc

CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

Front Tires 25 x 8-12, radial
Rear Tires 25 x 10-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

DETAILS

Park Brake Type

Overall Length 110.0 in
Overall Width 60.0 in
Overall Height 75.8 in

Curb Weight 1,594.2 lb* / 1,596.4 lb* CA Model

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps

reminder tamps

Additional Features Roof, Cast Aluminum Wheels

Color Choices Deep Blue





2025

MULE SX™





MSRP \$8,299

GRAYISH BLUE



SUPER BLACK



POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 20.6 lb-ft @ 2,200 rpm

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.3:1

Fuel System

Nikki 6C1026 carburetor

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with differential

lock

Engine Braking No

Alternator Output (max)

17 amp

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 22 x 9-10 **Rear Tires** 22 x 11-10

Steering Rack-and-pinion

Front Brakes Drum

Rear Brakes Drum **Park Brake Type** Independent, mechanical drum

399 lb

Ground Clearance 6.1 in

Fuel Capacity 4.2 gal

Turning Radius 10.8 ft

Cargo Bed **Dimensions (LxWxH)**

Cargo Bed Load

Capacity

926 lb **Payload Capacity**

Seating Capacity

1,100 lb*** **Towing Capacity**

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.1 in

Estimated Dry

Weight

927.9 lb**

Curb Weight 967.6 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Grayish Blue, Super Black **Color Choices**

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ***Requires optional hitch.

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

MULE SX™ 4x4





MSRP \$9,649

SUPER BLACK



GRAYISH BLUE



POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.6:1

Fuel Injection Fuel System

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive** with differential lock

No

Engine Braking

Alternator Output

CAPABILITY

22.9 amp

|--|

Front Suspension / **Wheel Travel**

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires

24 x 9-10

Rear Tires

24 x 11-10

Steering

Rack-and-pinion

Front Brakes

Drum

Rear Brakes

Drum



Park Brake Type Independent, mechanical drum **Ground Clearance** 6.7 in **Fuel Capacity** 4.2 gal **Turning Radius** 10.8 ft Cargo Bed 35.6 x 40.9 x 9.6 in **Dimensions (LxWxH) Cargo Bed Load** 399 lb **Capacity** 915 lb **Payload Capacity Seating Capacity** 1,100 lb*** **Towing Capacity** Lighting (2) Halogen headlights, tail/brake lights

DETAILS

Overall Length

Overall Width 52.6 in **Overall Height** 70.9 in 992.3 lb** **Estimated Dry** Weight **Curb Weight** 1,031.9 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

106.7 in

Color Choices Super Black, Grayish Blue

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ***Requires optional hitch.

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

MULE SX™ 4x4 FE





\$10,399



BRIGHT WHITE



POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

401cc **Displacement**

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.6:1

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output

with th	ilerentiat toc	ĸ	
No			
22.9 am	пр		

Park Brake Type Independent, mechanical drum

Ground Clearance 6.7 in

Fuel Capacity 4.2 gal

Turning Radius 10.8 ft

Cargo Bed Dimensions 35.6 x 40.9 x 9.6 in

(LxWxH)

Cargo Bed Load

Capacity

399 lb

Payload Capacity 915 lb

Seating Capacity

Towing Capacity 1,100 lb**

Lighting (2) Halogen headlights, tail/brake lights

CAPABILITY

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel**

Rear Suspension /

Unit Swingarm/3.1 in

Wheel Travel

24 x 9-10

Rear Tires

Steering

Front Tires

Rack-and-pinion

Front Brakes

Drum

Rear Brakes

24 x 11-10

Drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 72.4 in

Curb Weight 1,056.2 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Scan with camera to view videos, key features



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Requires optional hitch

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE I1194.

MULE SX™ 4x4 XC





\$9,949



METALLIC SIERRA BLUE



POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement

21.4 lb-ft @ 2,400 rpm **Maximum Torque**

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.6:1

Fuel Injection Fuel System

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking No

Alternator Output

(max)

22.9 amp

CAPABILITY

Front Suspension / **Wheel Travel**

MacPherson Strut/3.1 in

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires

26 x 9-12

Rear Tires 26 x 9-12

Steering Rack-and-pinion

Front Brakes

Drum

Rear Brakes

Scan with camera

to view videos.

key features

and more.

Drum



106.7 in

52.6 in

73.4 in


1,043.0 lb**

1,082.7 lb*

Metallic Sierra Blue

Fuel gauge, hour meter, oil temp light, parking brake

70.1 in



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ***Requires optional hitch.

DETAILS

Overall Length

Overall Width

Overall Height

Estimated Dry

Curb Weight

Wheelbase

Instruments

Weight

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

MULE SX™ 4x4 XC LE





\$10,999



ICE GRAY



POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 82.0 x 76.0mm

Compression Ratio 8.6:1

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive**

with differential lock

Engine Braking Nο

Alternator Output 22.9 amp

(max)

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in **Wheel Travel**

Rear Suspension /

Unit Swingarm/3.1 in Wheel Travel

Front Tires

26 x 9-12

Rear Tires

26 x 9-12

Steering

Rack-and-pinion

Front Brakes

Drum

Rear Brakes

Drum

Park Brake Type

Independent, mechanical drum

Ground Clearance 6.7 in

Fuel Capacity 4.2 gal

Turning Radius 11.8 ft

Cargo Bed

Dimensions (LxWxH)

399 lb

Cargo Bed Load Capacity

Payload Capacity 884 lb

Seating Capacity

1,100 lb*** **Towing Capacity**

Lighting (4) LED headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 75.0 in

1,058.4 lb** **Estimated Dry**

Weight

Curb Weight 1,098.1 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake light

Additional Features Roof, Under Seat Storage, LED Headlights, Painted Body

Panels

Color Choices Ice Gray

Scan with camera to view videos. key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ***Requires optional hitch.

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.