# Kawasaki

# Let the Good Times Roll®



# NINJA® 500





MSRP NON-ABS \$5,299

**MSRP ABS** 

\$5,699 - \$5,899



METALLIC MATTE WHITISH SILVER/METALLIC MOONDUST GRAY

Single 310mm semi-floating disc with 2-piston

Single 220mm disc with single-piston caliper (and



PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY



**Front Brakes** 

**Rear Brakes** 

**DETAILS** 

**Frame Type** 

Rake/Trail

**Overall Length** 

**Overall Width** 

**Overall Height** 

**Seat Height** 

Weight

**Estimated Dry** 

**Curb Weight** 

**Ground Clearance** 

METALLIC FLAT SPARK BLACK/METALLIC SPARK BLACK/ METALLIC MOONDUST GRAY



calipers (and ABS)

Trellis, high-tensile steel

24.5°/3.6 in

78.5 in

28.7 in

44.1 in

5.7 in

30.9 in

Model

3.7 gal

### **POWER**

4-stroke, Parallel Twin, DOHC, liquid-cooled **Engine** 

**Displacement** 451cc

**Bore x Stroke** 

70.0 x 58.6mm

**Compression Ratio** 

11 3.1

Maximum Horsepower 51.0 hp1 @ 10,000 rpm

**Maximum Torque** 

31.7 lb-ft @ 7,500 rpm

**Fuel System** 

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Digital Advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Aids

Economical Riding Indicator, Anti-lock Brake System

(ABS only)

# **PERFORMANCE**

Front Suspension / **Wheel Travel** 

41mm hydraulic telescopic fork/4.7 in

**Rear Suspension / Wheel Travel** 

Horizontal back-link with adjustable spring preload/5.1 in

**Front Tire** 

110/70-17

**Rear Tire** 

150/60-17

**Fuel Capacity** 

Wheelbase 54.1 in

**Special Features** 

ERGO-FIT®, LCD Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP

344.0 lb\*\* (ABS) / 346.2 lb\*\* (ABS) 50-State Model,

339.6 lb\*\* (non-ABS) / 341.8 lb\*\* (non-ABS) 50-State

374.9 lb\*(ABS) / 377.1 lb\* (ABS) 50-State Model, 370.4

lb\* (non-ABS) / 372.6 lb\* (non-ABS) 50-State Model

**Color Choices** 

Metallic Matte Whitish Silver/Metallic Moondust Gray, Passion Red/Metallic Flat Spark Black/Metallic Matte Dark Gray, Metallic Flat Spark Black/Metallic

Spark Black/Metallic Moondust Gray

Scan with camera to view videos. key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® 500 KRT EDITION





MSRP **\$5,499** 



LIME GREEN/EBONY/PEARL BLIZZARD WHITE



### **POWER**

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

**Bore x Stroke** 70.0 x 58.6mm

Compression

Ratio

11.3:1

Maximum

Horsepower

51.0 hp1 @ 10,000 rpm

31.7 lb-ft @ 7,500 rpm

Maximum Torque
Fuel System

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Digital Advance

Transmission

6-speed

Final Drive

Sealed chain

**Electronic Rider** 

Aids

**Economical Riding Indicator** 

# **PERFORMANCE**

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable spring preload/5.1 in

F ------

Front Tire 110/70-17

**Rear Tire** 150/60-17

Front Brakes Single 310mm semi-floating disc with 2-piston

calipers

**Rear Brakes** Single 220mm disc with single-piston caliper

### **DETAILS**

Frame Type Trellis, high-tensile steel

Rake/Trail 24.7°/3.6 in

Overall Length 78.5 in

Overall Width 28.7 in

Overall Height 44.1 in

**Ground Clearance** 5.7 in

Seat Height 30.9 in

**Estimated Dry** 

Weight

339.6 lb\*\* / 341.8 lb\*\* 50-State Model

**Curb Weight** 370.4 lb\* / 372.6 lb\* 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

**Special Features** ERGO-FIT®, LCD Instrumentation with Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green/Ebony/Pearl Blizzard White

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of

drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® 500 SE ABS





MSRP **\$6,399** 



METALLIC FLAT SPARK BLACK/METALLIC SPARK BLACK/METALLIC MOONDUST GRAY



PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY



#### **POWER**

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke

70.0 x 58.6mm

Compression

Ratio

11.3:1

Maximum Horsepower 51.0 hp<sup>1</sup> @ 10,000 rpm

**Maximum Torque** 

31.7 lb-ft @ 7,500 rpm

**Fuel System** 

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Digital Advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Electron

Economical Riding Indicator, Anti-lock Brake System (ARS)

# **PERFORMANCE**

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link with adjustable spring

ravel preload/5.1 in

**Front Tire** 

110/70-17

**Rear Tire** 

150/60-17

Front Brakes

Single 310mm semi-floating disc with 2-piston

calipers and ABS

**Rear Brakes** 

Single 220mm disc with single-piston caliper and

ABS

### **DETAILS**

Frame Type Trellis, high-tensile steel

Rake/Trail 24.7°/3.6 in

Overall Length 78.5 in

Overall Width 28.7 in

Overall Height 46.5 in

**Ground Clearance** 5.7 in

Seat Height 30.9 in

**Estimated Dry** 

**Fuel Capacity** 

Wheelbase

Weight

348.4 lb\*\* / 350.6 lb\*\* 50-State Model

**Curb Weight** 379.3 lb\* / 381.5 lb\* 50-State Model

3.7 gal

54.1 in

Special Features

ERGO-FIT®, Full-color TFT Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE APP, Kawasaki's Intelligent Proximity Activation Start

System (KIPASS), USB-C outlet

Color Choices

Metallic Flat Spark Black/Metallic Spark Black/ Metallic Moondust Gray, Passion Red/Metallic Flat

Spark Black/Metallic Matte Dark Gray

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of

drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® 500 SE KRT EDITION ABS





MSRP **\$6,399** 



LIME GREEN/EBONY/PEARL BLIZZARD WHITE



#### **POWER**

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke

70.0 x 58.6mm

Compression

Ratio

11.3:1

Maximum

Horsepower

51.0 hp<sup>1</sup> @ 10,000 rpm

**Maximum Torque** 

31.7 lb-ft @ 7,500 rpm

**Fuel System** 

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Digital Advance

Transmission

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Economical Riding Indicator, Anti-lock Brake System

(ARS)

# **PERFORMANCE**

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link with adjustable spring

Specifications subject to change. Visit Kawasaki.com for full product details.

preload/5.1 in

Front Tire

110/70-17

Rear Tire 150/60-17

**Front Brakes** 

Single 310mm semi-floating disc with 2-piston

calipers and ABS

**Rear Brakes** 

Single 220mm disc with single-piston caliper and

ABS

## **DETAILS**

Frame Type Trellis, high-tensile steel

Rake/Trail 24.7°/3.6 in

Overall Length 78.5 in

Overall Width 28.7 in

Overall Height 46.5 in

**Ground Clearance** 5.7 in

Seat Height 30.9 in

Weight

**Curb Weight** 

**Estimated Dry** 348.4 lb\*\* / 350.6 lb\*\* 50-State Model

379.3 lb\* / 381.5 lb\* 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features ERGO-FIT®, Full-color T

ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP, Kawasaki's Intelligent Proximity Activation Start

System (KIPASS), USB-C outlet

Color Choices Lime Green/Ebony/Pearl Blizzard White

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

# NINJA® 650





MSRP NON-ABS **MSRP ABS** \$7,399 \$7,999

CANDY STEEL FURNACE ORANGE/METALLIC SPARK BLACK/ METALLIC ROYAL PURPLE



METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK



METALLIC MATTE OLD SCHOOL GREEN/METALLIC SPARK BLACK



### **POWER**

4-stroke, parallel twin, DOHC, 8-valve, liquid **Engine** 

cooled

Displacement 649cc

**Bore x Stroke** 83.0 x 60.0mm

Compression

**Ratio** 

10.8:1

Maximum Horsepower 67.0 hp1 @ 8,000 rpm

**Maximum Torque** 

48.5 lb-ft @ 6,700 rpm

**Fuel System** 

DFI® with dual 36mm Keihin throttle bodies

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Kawasaki TRaction Control (KTRC), Anti-lock

Brake System (ABS only)

### **PERFORMANCE**

**Front Suspension** / Wheel Travel

41mm hydraulic telescopic fork/4.9 in

**Rear Suspension** / Wheel Travel

Horizontal back-link with adjustable spring

preload/5.1 in

**Front Tire** 120/70 x 17

**Rear Tire** 160/60 x 17

**Front Brakes** Dual 300mm petal-type discs and 2-piston

calipers (and ABS)

Single 220mm petal-type disc and single-piston **Rear Brakes** 

caliper (and ABS)

## **DETAILS**

**Frame Type** Trellis, high-tensile steel

Rake/Trail 24.0°/3.9 in

**Overall Length** 80.9 in

**Overall Width** 29.1 in

**Overall Height** 45.1 in

Ground Clearance 5.1 in

**Seat Height** 31.1 in

**Curb Weight** 423.4 lb\* (ABS), 421.2 lb\* (non-ABS)

**Fuel Capacity** 4.0 gal

Wheelbase 55.5 in

**Color Choices** 

Candy Steel Furnace Orange/Metallic Spark Black/Metallic Royal Purple, Metallic Matte Old School Green/Metallic Spark Black, Metallic Spark Black/Metalic Flat Spark Black

Scan with camera to view videos. key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change, Visit Kawasaki, com for full product details.

# NINJA® 650 KRT EDITION ABS





\$7,999



LIME GREEN/EBONY/PEARL BLIZZARD WHITE



### **POWER**

4-stroke, parallel twin, DOHC, 8-valve, liquid **Engine** 

cooled

10.8:1

Displacement 649cc

**Bore x Stroke** 83.0 x 60.0mm

Compression

**Ratio** Maximum

Horsepower

67.0 hp1 @ 8,000 rpm

**Maximum Torque** 

48.5 lb-ft @ 6,700 rpm

**Fuel System** 

DFI® with dual 36mm Keihin throttle bodies

Ignition

TCBI with electronic advance

**Transmission** 

6-speed

**Final Drive** 

Sealed chain

**Electronic Rider** 

Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS only)

**PERFORMANCE** 

**Front Suspension** / Wheel Travel

41mm hydraulic telescopic fork/4.9 in

**Rear Suspension** / Wheel Travel

Horizontal back-link with adjustable spring

preload/5.1 in

**Front Tire** 

120/70 x 17

**Rear Tire** 

160/60 x 17

**Front Brakes** 

Dual 300mm petal-type discs and 2-piston

calipers and ABS

**Rear Brakes** 

Single 220mm petal-type disc and single-piston

caliper and ABS

# **DETAILS**

**Frame Type** Trellis, high-tensile steel

80.9 in

Rake/Trail 24.0°/3.9 in

**Overall Length** 

**Overall Width** 29.1 in

**Overall Height** 45.1 in

Ground

Clearance

5.1 in

**Seat Height** 

31.1 in

**Curb Weight** 

423.4 lb\*

**Fuel Capacity** 

4.0 gal

Wheelbase

55.5 in

**Color Choices** 

Lime Green/Ebony/Pearl Blizzard White

Scan with camera to view videos, key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® 1100SX ABS





# \$13,699



METALLIC CARBON GRAY/METALLIC DIABLO BLACK



#### **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement

77.0 x 59.0mm Bore x Stroke

**Compression Ratio** 

Maximum Horsepower 134.0 hp1 @ 9,000 rpm

**Maximum Torque** 83.2 lb-ft @ 7,600 rpm

DFI® with 38mm Electronic Throttle Valves **Fuel System** 

Ignition TCBI with Digital Advance

6-speed, return shift with wet multi-disc manual Assist & **Transmission** 

Slipper Clutch

**Final Drive** Sealed chain

**Electronic Rider Aids** Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

**Enhanced Chassis Orientation Awareness** 

### **PERFORMANCE**

Front Suspension / **Wheel Travel** 

41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in

**Rear Suspension /** Horizontal back-link, gas-charged rear shock with rebound **Wheel Travel** damping, remotely adjustable spring preload/5.6 in

**Front Tire** 120/70-17

**Rear Tire** 190/50-17

**Front Brakes** Dual 300mm discs with radial-mount 4-piston monobloc

calipers, Kawasaki Intelligent anti-lock Brake System

(KIBS)

**Rear Brakes** Single 260mm disc with single-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

#### **DETAILS**

**Frame Type** Twin-spar aluminum

Rake/Trail 24.0°/3.9 in

**Overall Length** 82.7 in **Overall Width** 31.7 in

**Overall Height** 46.9 in/48.2 in w/ windshield high

**Ground Clearance** 5.3 in **Seat Height** 32.3 in

**Estimated Dry** Weight

471.9 lh\*\*

**Curb Weight** 518.2 lb\*

**Fuel Capacity** 5.0 gal

Wheelbase 56.7 in

**Special Features** 4.3" All-digital TFT Instrumentation, All-LED lighting, USB

Type-C outlet, Smartphone Connectivity with Voice Command via RIDEOLOGY THE APP MOTORCYCLE

**Color Choices** Metallic Carbon Gray/Metallic Diablo Black

Scan with camera to view videos. key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® 1100SX SE ABS





# \$15,399



EMERALD BLAZED GREEN/METALLIC DIABLO BLACK/ METALLIC GRAPHITE GRAY



EMERALD BLAZED GREEN/METALLIC DIABLO BLACK



#### **POWER**

Horsepower

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 1,099cc

**Bore x Stroke** 77.0 x 59.0mm

**Compression Ratio** 11.8:1

Maximum 134.0 hp1 @ 9,000 rpm

**Maximum Torque** 83.2 lb-ft @ 7,600 rpm

**Fuel System** DFI® with 38mm Electronic Throttle Valves

TCBI with Digital Advance Ignition

**Transmission** 6-speed, return shift with wet multi-disc manual Assist

& Slipper Clutch

**Final Drive** Sealed chain

**Electronic Rider** 

Aids

Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-**Enhanced Chassis Orientation Awareness** 

### PERFORMANCE

Front Suspension / **Wheel Travel** 

41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in

**Rear Suspension / Wheel Travel** 

Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping, remotely adjustable spring preload/5.6 in

Specifications subject to change. Visit Kawasaki.com for full product details.

**Front Tire** 120/70-17

**Rear Tire** 190/50-17

**Front Brakes** Dual 300mm discs with radial-mount 4-piston Brembo

M4.32 monobloc calipers, Kawasaki Intelligent anti-lock

Brake System (KIBS)

Single 260mm disc with single-piston caliper, Kawasaki **Rear Brakes** 

Intelligent anti-lock Brake System (KIBS)

### **DETAILS**

**Frame Type** Twin-spar aluminum

24.0°/3.9 in Rake/Trail

**Overall Length** 82.7 in

**Overall Width** 31.7 in

**Overall Height** 46.9 in/48.2 in w/ windshield high

**Ground Clearance** 5.3 in

**Seat Height** 32.3 in

**Estimated Dry** 469.7 lb\*\*

Weight

**Curb Weight** 516.0 lb\*

**Fuel Capacity** 

Wheelbase 56.7 in

**Special Features** 

4.3" All-digital TFT Instrumentation, All-LED lighting, USB Type-C outlet, Grip heaters, Smartphone Connectivity

with Voice Command via RIDEOLOGY THE APP

MOTORCYCLE

5.0 gal

**Color Choices** Emerald Blazed Green/Metallic Diablo Black

Scan with camera to view videos. key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

# NINJA H2® ABS





### MSRP **\$32,700**



MIRROR COATED SPARK BLACK



#### **POWER**

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 8.5:1

Maximum 239.6 hp<sup>1</sup> @ 11,500 rpm

Horsepower

Maximum Torque

104.9 lb-ft @ 11,000 rpm

**Fuel System** 

DFI® with 50mm throttle bodies (4) with dual injection;

Kawasaki Supercharger

Ignition

TCBI with Digital Advance

Transmission

6-speed, return shift, dog-ring

Final Drive

Sealed chain

**Electronic Rider Aids** 

Economical Riding Indicator, Kawasaki Cornering
Management Function (KCMF), Kawasaki TRaction Control
(KTRC), Kawasaki Launch Control Mode (KLCM), IMUEnhanced Chassis Orientation Awareness, Kawasaki
Intelligent anti-lock Brake System (KIBS), Kawasaki Engine
Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift
& downshift), Öhlins Electronic Steering Damper

### **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Specifications subject to change. Visit Kawasaki.com for full product details.

Rear Suspension /

Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and topoutspring/5.3 in

Front Tire 120/70-17

Rear Tire 200/55-17

Front Brakes Dual 330mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 250mm disc with opposed 2-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

### **DETAILS**

Frame Type Trellis, high-tensile steel, with swingarm mounting plate

Rake/Trail 24.5°/4.1 in

Overall Length 82.1 in

Overall Width 30.3 in

Overall Height 44.3 in

Ground Clearance 5.1 in

Seat Height 32.5 in

Estimated Dry Weight 480.7 lb\*\*

Curb Weight 524.8 lb\*

Fuel Capacity 4.5 gal

Wheelbase 57.3 in

Special Features Supercharged engine, All-digital TFT color Instrumentation,

All-LED lighting, Highly Durable Paint, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Mirror Coated Spark Black

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

# NINJA H2® CARBON ABS





### MSRP **\$36,200**



MIRROR COATED MATTE SPARK BLACK/ CANDY FLAT BLAZED GREEN



#### **POWFR**

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 8.5:

**Maximum Torque** 

Maximum Horsepower 239.6 hp<sup>1</sup> @ 11,500 rpm

Fuel System DFI® with 50mm throttle bodies (4) with dual injection;

104.9 lb-ft @ 11,000 rpm

Kawasaki Supercharger

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift, dog-ring

Final Drive Sealed chain

**Electronic Rider Aids** Economical Riding Indicator, Kawasaki Cornering Management

Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins

**Electronic Steering Damper** 

#### **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback wheel Travel reservoir, 24-way compression and rebound damping adjustability. 15-way spring preload adjustability, and top-

adjustability, 15-way spring preload adjustability, and topoutspring/5.3 in

Front Tire 120/70-17

Rear Tire 200/55-17

Front Brakes Dual 330mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki

Intelligent anti-lock Brake System (KIBS)

**Rear Brakes** Single 250mm disc with opposed 2-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

#### **DETAILS**

Frame Type Trellis, high-tensile steel, with swingarm mounting plate

Rake/Trail 24.5°/4.1 in

Overall Length 82.1 in

Overall Width 30.3 in

Overall Height 44.3 in

Ground Clearance 5.1 in

Seat Height 32.5 in

Estimated Dry Weight 480.7 lb\*\*

Curb Weight 524.8 lb\*

Fuel Capacity 4.5 gal

Wheelbase 57.3 in

Special Features Supercharged engine, All-digital TFT color Instrumentation,

All-LED lighting, Carbon fiber, Highly Durable Paint, Serial number stamp, Smartphone Connectivity via RIDEOLOGY THE

Color Choices Mirror Coated Matte Spark Black/Candy Flat Blazed Green

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA H2®R ABS





### **MSRP** \$59,100



MIRROR COATED MATTE SPARK BLACK



#### **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

**Bore x Stroke** 

**Compression Ratio** 

Maximum

Horsepower

**Maximum Torque** 

**Fuel System** 

Ignition

**Transmission** 

**Final Drive** 

**Electronic Rider Aids** 

8.3:1

76.0 x 55.0mm

321.5 hp1 @ 14,000 rpm

121.5 lb-ft @ 12,500 rpm

DFI® with 50mm throttle bodies (4) with dual injection;

Kawasaki Supercharger

TCBI with Digital Advance

6-speed, return shift, dog-ring

Sealed chain

Economical Riding Indicator, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift

& downshift), Öhlins Electronic Steering Damper

### **PERFORMANCE**

Front Suspension / **Wheel Travel** 

43mm inverted Kavaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Specifications subject to change. Visit Kawasaki.com for full product details.

Rear Suspension / Wheel Travel

Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback reservoir, 30-way compression and rebound damping adjustability, 16-way spring preload adjustability, and topoutspring/5.3 in

**Front Tire** 120/60-17 V01F slick

**Rear Tire** 190/65-17 V01R slick

**Front Brakes** Dual 330mm semi-floating discs with dual radial-mount, opposed 4-piston Brembo M50 Monobloc calipers, Kawasaki

Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 250mm disc with opposed 2-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

### **DETAILS**

**Overall Length** 

Trellis, high-tensile steel, with swingarm mounting plate **Frame Type** 

Rake/Trail 25.1° / 4.3 in

81.5 in

**Overall Width** 33.5 in

**Overall Height** 45.7 in

**Ground Clearance** 5.1 in **Seat Height** 32.7 in

**Estimated Dry Weight** 432.2 lb\*\*

**Curb Weight** 476.3 lb\*

**Fuel Capacity** 4.5 gal Wheelbase 57.1 in

**Special Features** Supercharged engine, Carbon fiber aerodynamic downforce

generating devices, Highly Durable Paint

**Color Choices** Mirror Coated Matte Spark Black

Scan with camera to view videos. key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

# NINJA H2® SX SE ABS





### MSRP **\$29,100**



EMERALD BLAZED GREEN/METALLIC DIABLO BLACK/METALLIC MATTE GRAPHENESTEEL GRAY



#### **POWER**

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

11.2:1

Compression Ratio

Maximum Horsepower 207.0 hp<sup>1</sup> @ 10,000 rpm

**Maximum Torque** 

101.0 lb-ft @ 8,500 rpm

Fuel System

DFI® with 40mm throttle bodies (4); Kawasaki Supercharger

Ignition

TCBI with Digital Advance

Transmission

6-speed, return shift, dog-ring

**Final Drive** 

Sealed chain

**Electronic Rider Aids** 

Economical Riding Indicator, Advanced Rider Assistance Systems (ARAS): Forward Collision Warning (FCW), Blind-Spot Detection (BSD), Adaptive Cruise Control (ACC). Vehicle Hold Assist (VHA), Kawasaki Electronic Control Suspension with Showa Skyhook Technology (KECS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (dual direction), IMU-Enhanced Chassis Orientation Awareness

### **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel Uni-Trak®, Showa BFRC lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring

preload/5.5 inspring/5.3 in

Front Tire 120/70-17

Rear Tire 190/55-17

Front Brakes Dual 320mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki

Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 250mm disc with opposed 2-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

#### **DETAILS**

| Frame Type     | irellis, nign-tensile steel, with swingarm mounting plate |
|----------------|---|
| Rake/Trail     | 24.7°/4.1 in  |
| Overall Length | 85.6 in   |

Overall Width 31.1 in

Overall Height 49.6 in

Ground Clearance 5.1 in

Seat Height 32.9 in

Curb Weight 590.9 lb\*
Fuel Capacity 5.0 gal

Wheelbase 58.3 in

**Special Features** 

Supercharged engine, 6.5" Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), Highly Durable Paint, Grip heaters, Tire Pressure Monitoring System (TPMS), Smartphone Connectivity via Kawasaki SPIN

infotainment app

Color Choices Emerald Blazed Green/Metallic Diablo Black/Metallic Matte

Graphenesteel Gray

Scan with camera to view videos, key features and more.



# NINJA® ZX™-4R ABS





\$8,999



METALLIC SPARK BLACK



### **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve,

liquid-cooled

Displacement 399cc

**Bore x Stroke** 57.0 x 39.1mm

Compression 12.3:1

Ratio

Horsepower

Maximum 56.0 hp1 @ 11,500 rpm

**Maximum Torque** 26.5 lb-ft @ 11,000 rpm

**Fuel System** DFI® with 34mm throttle valves (4)

TCBI with Digital Advance Ignition

**Transmission** 6-speed, return shift

**Final Drive** Chain

**Electronic Rider** 

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock

Brake System (ABS)

# **PERFORMANCE**

**Front Suspension** / Wheel Travel

37mm inverted Showa fork with SFF-BP internals/4.7 in

**Rear Suspension** / Wheel Travel

**Front Tire** 

Horizontal back-link, Showa shock w/ adjustable spring preload/4.4 in

**Rear Tire** 160/60-17

**Front Brakes** 

110/70-17

Dual 290mm semi-floating discs with radialmount 4-piston monobloc caliper and ABS

Single 220mm disc with single-piston caliper and **Rear Brakes** 

# **DETAILS**

Trellis, high-tensile steel **Frame Type** 

Rake/Trail 23.5°/3.8 in

**Overall Length** 78.3 in

**Overall Width** 30.1 in

**Overall Height** 43.7 in

**Ground Clearance** 5.3 in

**Seat Height** 31.5 in

**Curb Weight** 414.5 lb\*

**Fuel Capacity** 4.0 gal

Wheelbase 54.3 in

**Special Features** 4.3" Full-color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** Metallic Spark Black





# NINJA® ZX™-4RR ABS





\$9,699



METALLIC MATTE WHITISH SILVER/ METALLIC FLAT SPARK BLACK



### **POWER**

4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-**Engine** 

**Displacement** 399cc

**Bore x Stroke** 57.0 x 39.1mm

**Compression Ratio** 

12.3:1

Maximum Horsepower 56.0 hp1 @ 11,500 rpm

**Maximum Torque** 26.5 lb-ft @ 11,000 rpm

DFI® with 34mm throttle valves (4) **Fuel System** 

Ignition TCBI with Digital Advance

**Transmission** 6-speed, return shift

**Final Drive** Chain

**Electronic Rider** 

Aids

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock Brake

System (ABS)

### PERFORMANCE

Front Suspension / Wheel Travel

37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in

**Rear Suspension / Wheel Travel** 

Horizontal back-link, Showa BFRC lite gas-charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in

110/70-17 **Front Tire Rear Tire** 160/60-17

**Front Brakes** Dual 290mm semi-floating discs with radial-mount 4-

piston monobloc caliper and ABS

**Rear Brakes** Single 220mm disc with single-piston caliper and ABS

### **DETAILS**

Trellis, high-tensile steel **Frame Type** 

Rake/Trail 23.5°/3.8 in

**Overall Length** 78.3 in

**Overall Width** 30.1 in

**Overall Height** 43.7 in

**Ground Clearance** 5.3 in

**Seat Height** 31.5 in

**Curb Weight** 414.5 lb\*

**Fuel Capacity** 4.0 gal

Wheelbase 54.3 in

**Special Features** 4.3" Full-color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Metallic Matte Whitish Silver/Metallic Flat Spark **Color Choices** 

Black

Scan with camera to view videos. key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb. 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of

many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings, Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A Specifications subject to change, Visit Kawasaki, com for full product details.

# NINJA® ZX™-4RR KRT EDITION ABS





\$9,699



LIME GREEN/EBONY/PEARL BLIZZARD WHITE



### **POWER**

**Engine** 4-stroke, in-line 4-cylinder, DOHC, 16-valve,

liquid-cooled

Displacement 399cc

**Bore x Stroke** 57.0 x 39.1mm

Compression

Ratio

12.3:1

Maximum Horsepower

56.0 hp1 @ 11,500 rpm

**Maximum Torque** 

26.5 lb-ft @ 11,000 rpm

**Fuel System** 

DFI® with 34mm throttle valves (4)

Ignition

TCBI with Digital Advance

**Transmission** 

6-speed, return shift

**Final Drive** 

Chain

**Electronic Rider** 

**Aids** 

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock

Brake System (ABS)

# **PERFORMANCE**

Front Suspension / Wheel Travel

37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in

**Rear Suspension** / Wheel Travel

Horizontal back-link, Showa BFRC lite gascharged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in

**Rear Brakes** 

**Front Tire** 

**Rear Tire** 

110/70-17 160/60-17

**Front Brakes** Dual 290mm semi-floating discs with radialmount 4-piston monobloc caliper and ABS

Single 220mm disc with single-piston caliper and

### **DETAILS**

**Frame Type** Trellis, high-tensile steel

Rake/Trail 23.5°/3.8 in

**Overall Length** 78.3 in

**Overall Width** 30.1 in

**Overall Height** 43.7 in

**Ground Clearance** 5.3 in

**Seat Height** 31.5 in

**Curb Weight** 414.5 lb\*

**Fuel Capacity** 4.0 gal

Wheelbase 54.3 in

**Special Features** 4.3" Full-color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

**Color Choices** Lime Green/Ebony/Pearl Blizzard White





Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of

drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® ZX™-6R





MSRP NON-ABS MSRP ABS **\$11,399** 

PEARL ROBOTIC WHITE/METALLIC GRAPHITE GRAY



METALLIC MATTE DARK GRAY/EBONY



#### **POWER**

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression Ratio 12.9:1

Maximum 127.0 hp<sup>1</sup> @ 13,000 rpm

Horsepower

, , , ,

Maximum Torque 52.1 lb-ft @ 10,800 rpm

Fuel System DFI® with 38mm Keihin throttle bodies (4) and oval sub-

throttles

Ignition TCBI with electronic advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Aids Kawasaki Traction Control (KTRC), Power Modes (Full/

Low), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter (KQS) (upshift only)

#### **PERFORMANCE**

Front Suspension / Wheel Travel

41mm inverted fork Showa Separate Function Big Piston Fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs/4.7

in

Rear Suspension / Wheel Travel Bottom-link Uni-Trak® with single shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring preload/5.9 in

Front Tire 120/70 ZR17

Rear Tire 180/55 ZR17

Front Brakes Dual semi-floating 310mm discs with dual radial-

mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)

**Rear Brakes** Single 220mm petal discs with single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS

onlv)

#### **DETAILS**

| Frame Type       | Aluminum perimeter |
|------------------|--------------------|
| Rake/Trail       | 23.5°/4.0 in       |
| Overall Length   | 79.7 in            |
| Overall Width    | 28.0 in            |
| Overall Height   | 43.3 in            |
| Ground Clearance | 5.1 in             |
| Seat Height      | 32.7 in            |

Curb Weight 436.6 lb\* (ABS), 432.2 lb\* (non-ABS) 50-State Model, 434.4

lb\* (ABS), 430.0 lb\* (non-ABS) 49-State Model

Fuel Capacity 4.5 gal
Wheelbase 55.1 in

Wileetbase 33.1 III

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLOGY THE APP

**Color Choices** Pearl Robotic White/Metallic Graphite Gray, Metallic

Matte Dark Gray/Ebony

Scan with camera to view videos, key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of

many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® ZX™-6R KRT EDITION





MSRP NON-ABS MSRP ABS **\$11,399** 



LIME GREEN/EBONY/PEARL BLIZZARD WHITE



#### **POWER**

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 636cc

Bore x Stroke 67.0 x 45.1mm

Compression Ratio 12.9:1

Maximum 127.0 hp<sup>1</sup> @ 13,000 rpm

Horsepower

Maximum Torque

maximum rorque

Fuel System

throttles

Ignition TCBI with electronic advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Aids Kawasaki Traction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS)

52.1 lb-ft @ 10,800 rpm

(ABS only), Kawasaki Quick Shifter (KQS) (upshift only)

DFI® with 38mm Keihin throttle bodies (4) and oval sub-

#### **PERFORMANCE**

Front Suspension / Wheel Travel

41mm inverted fork Showa Separate Function Big Piston Fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs/4.7

in

Rear Suspension / Wheel Travel

Bottom-link Uni-Trak® with single shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring preload/5.9 in

Front Tire 120/70 ZR17

Rear Tire

Front Brakes Dual s

Dual semi-floating 310mm discs with dual radialmounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)

intettigent anti-tock brake system (kibs) (Abs only)

Rear Brakes Single 220mm petal discs with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS

only)

180/55 ZR17

### **DETAILS**

Frame Type

Rake/Trail

Overall Length

Overall Width

Overall Height

Ground Clearance

Seat Height

Aluminum perimeter

23.5°/4.0 in

79.7 in

28.0 in

43.3 in

5.1 in

32.7 in

Curb Weight 436.6 lb\* (ABS), 432.2 lb\* (non-ABS) 50-State Model, 434.4

lb\* (ABS), 430.0 lb\* (non-ABS) 49-State Model

Fuel Capacity 4.5 gal
Wheelbase 55.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Lime Green/Ebony/Pearl Blizzard White

Scan with camera to view videos, key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of

many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® ZX™-10RR ABS





MSRP **\$30,499** 



METALLIC MATTE GRAPHENESTEEL GRAY



#### **POWER**

Horsepower

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

**Displacement** 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 13.0:1

Maximum 188.0 hp<sup>1</sup> @ 11,500 rpm

Maximum Torque 81.7 lb-ft @ 11,500 rpm

Fuel System DFI®, 47mm throttle bodies and Variable Air Intake

System (VAI)

**Ignition** TCBI with digital advance

**Transmission** 6-speed, return shift

Final Drive Sealed chain

Julian States

Electronic Rider

Öhlins Electronic Steering Damper, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF), Power Modes

(Full/Mid/Low)

### **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Showa Balance Free Fork (BFF), adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite shock, stepless, dual-range (low-/ high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo dual semi-floating 330mm discs with dual radial

mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 220mm disc with aluminum single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

### **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 25.0°/4.1 in

Overall Length 82.1 in

Overall Width 29.5 in
Overall Height 46.7 in

Ground Clearance 5.3 in

Seat Height 32.9 in

Curb Weight 456.4 lb\*
Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Matte Graphenesteel Gray

Scan with camera to view videos, key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

# NINJA® ZX™-14R ABS





# \$17,599



METALLIC MATTE SOVEREIGN RED/METALLIC FLAT SPARK METALLIC MATTE GRAPHITE GRAY



### **POWER**

4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-**Engine** 

cooled

12.3:1

**Displacement** 1,441cc

84.0 x 65.0mm **Bore x Stroke** 

Compression

**Ratio** 

Maximum Horsepower 197.0 hp1 @ 10,000 rpm

**Maximum Torque** 

116.5 lb-ft @ 7,500 rpm

**Fuel System** 

DFI® with 44mm Mikuni throttle bodies (4)

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed, return shift

**Final Drive** 

Sealed chain

**Electronic Rider** 

**Aids** 

Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock

Brake System (ABS)

### **PERFORMANCE**

**Front Suspension** / Wheel Travel

43mm inverted cartridge fork with adjustable preload, 18-way compression and 15-way rebound damping adjustment/4.6 in

**Rear Suspension / Wheel Travel** 

Bottom-link Uni-Trak® and gas-charged shock with adjustable preload, stepless rebound and compression damping adjustments, adjustable ride

height/4.9 in

120/70-17

**Front Tire** 

**Rear Tire** 190/50-R17

**Front Brakes** 

Dual 310mm semi-floating Brembo discs with dual radial-mounted Brembo 4-piston M50 monobloc

calipers and ABS

**Rear Brakes** 

Single 250mm disc with twin-piston caliper and ABS

### **DETAILS**

**Frame Type** Aluminum monocoque

Rake/Trail 23.0°/3.7 in

**Overall Length** 85.4 in

**Overall Width** 30.3 in

**Overall Height** 46.1 in

**Ground Clearance** 4.9 in

**Seat Height** 31.5 in

**Curb Weight** 593.1 lb\*

**Fuel Capacity** 5.8 gal

Wheelbase 58.3 in

**Color Choices** Metallic Matte Sovereign Red/Metallic Flat Spark

Black/Metallic Matte Graphite Grav

Scan with camera to view videos. key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings, Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change, Visit Kawasaki, com for full product details.