Kawasaki

Let the Good Times Roll®



2025 TEDVV 4"

TERYX4[™]





MSRP **\$16,199**



NEON YELLOW/SUPER BLACK



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with (2) 36mm Mikuni throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Rear Brakes Sealed, oil-bathed, multi-disc

Ground Clearance 11.2 in
Fuel Capacity 7.9 gal

Fuel Capacity 7.9 gal
Turning Radius 16.7 ft

Cargo Bed 17.9 x 47.6 x 8.7 in

Dimensions (LxWxH)

249 lb

Cargo Bed Load Capacity

Payload Capacity 1,109 lb

Seating Capacity 4

Towing Capacity 1,300 lb

Lighting (2) incandescent headlights, (2) LED taillights, LED

stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double Wishbone; FOX Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in

Rear Suspension / Wheel Travel

Double Wishbone; FOX Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.3 in

Front Tires Maxxis® 26 x 9-12

Rear Tires Maxxis® 26 x 11-12

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

DETAILS

Overall Height

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in
Overall Width 60.0 in

Curb Weight 1,605.2 lb* / 1,607.4 lb* CA Model

77.8 in

Wheelbase 85.6 in

Instruments Multi-function digital meter with speedometer, fuel

gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Wheel Type Steel

Color Choices Neon Yellow/Super Black





TERYX4™ S CAMO





\$16,799



TRUETIMBER® STRATA



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio

Fuel System DFI® with (2) 36mm Mikuni throttle bodies

Ignition TCBI with electronic advance

10.7:1

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

Rear Brakes Sealed, oil-bathed, multi-disc

Ground Clearance 12.2 in (max) / 11.2 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 17.7 ft

17.9 x 47.6 x 8.7 in

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load Capacity

249 lb

Payload Capacity 1,000 lb

Seating Capacity

Towing Capacity 1.300 lb

Lighting (4) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

DETAILS

Overall Height

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in **Overall Width** 62.6 in

80.5 in **Curb Weight** 1,638.3 lb* / 1,640.5 lb* CA Model

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-

brake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Wheel Type Alloy **Additional Features** Roof

Color Choices TRUETIMBER® STRATA

Scan with camera to view videos. key features and more.



TERYX4™ S LE





\$17,499 - \$17,699

ICE GRAY/SUPER BLACK



METALLIC MATTE TWILIGHT BLUE/SUPER BLACK



CYPHER CAMO GRAY/SUPER BLACK



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

DFI® with (2) 36mm Mikuni throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System Flectric

Automatic CVT with centrifugal clutch (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

Ground Clearance 11.2 in / 12.2 in

Fuel Capacity 7.9 gal

Turning Radius 17.7 ft

Cargo Bed

Dimensions (LxWxH)

17.9 x 47.6 x 8.7 in

Cargo Bed Load

Capacity

249 lb

1,000 lb

Payload Capacity

Seating Capacity

Towing Capacity 1,300 lb

Lighting (4) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / Wheel Travel

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in **Overall Width** 62.6 in

Overall Height 80.5 in

Curb Weight 1,638.3 lb* / 1,640.5 lb* CA Model

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel

> gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Wheel Type Alloy

Additional Features Roof

Color Choices Ice Gray/Super Black, Metallic Matte Twilight Blue/Super

Black, Cypher Camo Gray/Super Black





TERYX4™ S SE





\$18,999



CANDY LIME GREEN/SUPER BLACK



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

DFI® with (2) 36mm Mikuni throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

Ground Clearance 12.2 in (max) / 11.2 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 17.7 ft

Cargo Bed

Dimensions (LxWxH)

249 lb

Cargo Bed Load Capacity

17.9 x 47.6 x 8.7 in

Payload Capacity 1,054 lb

Seating Capacity

Towing Capacity 1,300 lb

Lighting (4) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / Wheel Travel

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in

Overall Width 62.6 in **Overall Height** 80.5 in

Curb Weight 1,684.6 lb* / 1,686.8 lb* CA Model

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel

gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Wheel Type Alloy

Additional Features Roof, Hifonics® Bluetooth®/AM/FM Audio System,

WARN® VRX 35 Winch

Color Choices Candy Lime Green/Super Black





TERYX® KRX4™ 1000





\$24,999



METALLIC LIGHT GRAY/SUPER BLACK



METALLIC SIERRA BLUE/SUPER BLACK



POWFR

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System

Automatic CVT with centrifugal clutch (H,L,N,R) Transmission

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with 2-piston calipers Front Brakes

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal 23.3 ft **Turning Radius**

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

14.6 x 33.1 x 9.1 in

351 lb

1,001 lb

4

N/A

(2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Curb Weight

Frame Ladder type, tubular steel

Overall Length 157.3 in **Overall Width** 68.1 in **Overall Height** 76.2 in

Estimated Dry Weight 1,997.7 lb** / 1,999.9 lb** CA Model

2,099.2 lb* / 2,101.4 lb* CA Model

Wheelbase 125.8 in

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD +Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and

Wheel Type

Additional Features Steel skid-plates w/ drain holes

Color Choices Metallic Light Gray/Super Black, Metallic Sierra Blue/Super Black

CVT belt warning lamp

Scan with camera to view videos. key features and more.



TERYX® KRX4™ 1000 BLACKOUT EDITION





\$28,999



FLAT EBONY



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

TCBI with electronic advance Ignition

Starting System

Automatic CVT with centrifugal clutch (H,L,N,R) Transmission

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10 00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 13.8 in (max), 13.2 in (std)

Fuel Capacity 10.6 gal **Turning Radius** 23.3 ft

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

4 **Seating Capacity**

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light

351 lb

1,001 lb

14.6 x 33.1 x 9.1 in

DETAILS

Overall Height

Frame Ladder type, tubular steel

Overall Length 160 4 in **Overall Width** 68.1 in

78.0 in **Estimated Dry Weight** 2,152.1 lb** / 2,154.3 lb** CA Model

2,253.5 lb* / 2,257.7 lb* CA Model **Curb Weight**

Wheelbase

Instruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator

(L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp,

EPS warning lamp, and CVT belt warning lamp

Wheel Type

Additional Features

LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium

Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch

Color Choices Flat Ebony

Scan with camera to view videos, key features and more.



TERYX® KRX4™ 1000 eS





\$26,499



MATTE WHITISH SAND BEIGE/METALLIC FLAT RAW GRAYSTONE



POWFR

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System

Automatic CVT with centrifugal clutch (H,L,N,R) Transmission

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

CAPABILITY

Front Suspension /

Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and

KECS controlled compression damping/18.6 in

Rear Suspension /

Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable

preload, and KECS controlled compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with 2-piston calipers Front Brakes

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 15.2 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal **Turning Radius** 23.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in

(LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

4

Towing Capacity N/A

(2) LED headlights, (2) LED taillights, LED stoplight Lighting

DETAILS

Frame Ladder type, tubular steel

351 lb

1.001 lb

Overall Length 157.3 in **Overall Width** 68.1 in **Overall Height** 76.2 in

Estimated Dry Weight 2,006.6 lb** / 2,008.8 lb** CA Model

2,108.0 lb* / 2,110.2 lb* CA Model **Curb Weight**

Wheelbase 125.8 in

Instruments Multi-function digital meter with bar-style tachometer (2 display

options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD +Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and

CVT belt warning lamp

Wheel Type

Additional Features Steel skid-plates w/ drain holes, TFT Full-Color Instrumentation

with Smartphone Connectivity

Color Choices Matte Whitish Sand Beige/Metallic Flat Raw Graystone

Scan with camera to view videos. key features



TERYX® KRX4™ 1000 LIFTED EDITION





MSRP **\$27,999**



LIME GREEN/SUPER BLACK



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

Turning Radius 23.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load 351 lb

Payload Capacity

1,001 lb

Seating Capacity 4

Towing Capacity N/

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-

position adjustable compression damping/21.1 in

 Front Tires
 ITP Cryptid 32 x 10.00R15 6PR

 Rear Tires
 ITP Cryptid 32 x 10.00R15 6PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal

DETAILS

Curb Weight

Frame Ladder type, tubular steel

Overall Length 160.4 in
Overall Width 68.1 in

Overall Height 76.6 in

Wheelbase 125.8 in

123.0 11

Instruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge,

2,231.1 lb* / 2,233.3 lb* CA Model

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp

Wheel Type Allo

Additional Features Elevated snorkel intakes and CVT exhaust duct, Wide fender

flares, Front Bumper, F/R Tow Hooks, Steel skid-plates w/ drain holes, Rear view mirror, WARN® VRX 45-S Powersport Winch

Color Choices Lime Green/Super Black





TERYX KRX® 1000





MSRP \$21,199



METALLIC SIERRA BLUE/SUPER BLACK



METALLIC LIGHT GRAY/SUPER BLACK



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System

Automatic CVT with centrifugal clutch (H,L,N,R) Transmission

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Dual hydraulic discs with 2-piston calipers Front Brakes

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max) / 14.2 in (std)

Fuel Capacity 10.6 gal 20.3 ft **Turning Radius**

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load 351 lb Capacity

Payload Capacity 781 lb

Seating Capacity

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Curb Weight

Frame Ladder type, tubular steel

2

Overall Length 130.1 in **Overall Width** 68.1 in **Overall Height** 74.8 in

Estimated Dry Weight 1,794.9 lb** / 1,797.1 lb** CA Model 1.894.1 lb* / 1.896.3 lb* CA Model

Wheelbase 98.8 in

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD +Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and

Wheel Type Alloy with bead-lock wheels

Additional Features Steel skid-plates w/ drain holes

CVT belt warning lamp

Color Choices Metallic Sierra Blue/Super Black, Metallic Light Gray/Super Black

Scan with camera to view videos. key features and more.



TERYX KRX® 1000 BLACKOUT EDITION





\$24,999



FLAT EBONY



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking

Flectric

CAPABILITY

Front Suspension / Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback Wheel Travel reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position **Wheel Travel**

adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes Dual hydraulic discs with 2-piston calipers

Dual hydraulic discs with single-piston calipers Rear Brakes

Ground Clearance 14.0 in (max), 13.4 in (std)

Fuel Capacity 10.6 gal **Turning Radius** 20.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load 351 lh Capacity

781 lb **Payload Capacity**

Seating Capacity 2 **Towing Capacity**

Lighting (2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light

2,030.8 lb* / 2,033.0 lb* CA Model

DETAILS

Curb Weight

Instruments

Ladder type, tubular steel

Overall Length 133.3 in **Overall Width** 68.1 in **Overall Height** 76.0 in

Estimated Dry Weight 1,931.6 lb** / 1,933.8 lb** CA Model

Wheelbase

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-

style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp,

EPS warning lamp, and CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

Additional Features LED light bars (38-in mounted to front of roof, 8-in mounted to

front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch

Color Choices Flat Ebony

Scan with camera to view videos. key features



TERYX KRX® 1000 eS





MSRP **\$23,699**



MATTE WHITISH SAND BEIGE/METALLIC FLAT RAW GRAYSTONE



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and

KECS controlled compression damping/18.6 in

Rear Suspension / Wheel Travel 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 14.0 in (std)

Fuel Capacity 10.6 gal
Turning Radius 20.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load 351 lb Capacity

Payload Capacity 781 lb
Seating Capacity 2
Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Frame Ladder type, tubular steel

Overall Length 132.1 in
Overall Width 68.1 in
Overall Height 77.0 in

Estimated Dry Weight 1,839.0 lb** / 1,841.2 lb** CA Model

Curb Weight 1,938.2 lb* / 1,940.4 lb* CA Model

Wheelbase 98.8 in

Instruments Mult

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

Additional Features KQR™ Sport Roof, Front Bumper, Steel skid-plates w/ drain holes, TFT Full-Color Instrumentation with Smartphone

Connectivity

Color Choices Matte Whitish Sand Beige/Metallic Flat Raw Graystone

Scan with camera to view videos, key features



TERYX KRX® 1000 LIFTED EDITION





\$23,999



LIME GREEN/SUPER BLACK



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

DFI® with (2) 50mm throttle bodies **Fuel System**

TCBI with electronic advance Ignition

Starting System

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes **Cargo Bed Dimensions**

14.6 x 33.1 x 9.1 in (LxWxH)

Cargo Bed Load Capacity

Turning Radius

351 lb

Payload Capacity

781 lb

20.3 ft

Seating Capacity

2

Towing Capacity

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

ITP Cryptid 32 x 10.00R15 6PR

Rear Suspension / Wheel Travel

Rear Tires

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-

position adjustable compression damping/21.1 in

Front Tires ITP Cryptid 32 x 10.00R15 6PR

Electric Power Steering (EPS) / rack-and-pinion **Steering**

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 15.0 in (max), 14.4 in (std)

Fuel Capacity 10.6 gal

DETAILS

Frame Ladder type, tubular steel

Overall Length 132 9 in

Overall Width 68.1 in **Overall Height** 75.4 in

Curb Weight 2,006.6 lb* / 2,008.8 lb* CA Model

Wheelbase

Instruments Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge,

> gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp

Wheel Type

Additional Features Elevated snorkel intakes and CVT exhaust duct, Wide fender

flares, Front Bumper, F/R Tow Hooks, Steel skid-plates w/ drain holes, Rear view mirror, WARN® VRX 45-S Powersport Winch

Color Choices Lime Green/Super Black





TERYX KRX® 1000 TRAIL EDITION





MSRP **\$23,699**



CYPHER CAMO GRAY/SUPER BLACK



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and

24-position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.2 in (max) / 13.6 in (std)

Fuel Capacity 10.6 gal

Turning Radius 20.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in

(LxWxH)

Cargo Bed Load Capacity 351 lb

Payload Capacity

781 lb

Seating Capacity 2

Towing Capacity N/A

Lighting

(2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Frame Ladder type, tubular steel

Overall Length 133.3 in
Overall Width 68.1 in
Overall Height 76.6 in

Curb Weight 2,017.6 lb* / 2,019.8 lb* CA Model

Wheelbase 98.8 i

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp,

water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

Additional Features KQR™ Sport Roof, Front Bumper, Rear Bumper, Nerf Bars,

Steel skid-plates w/ drain holes, WARN® VRX 45 Powersport

Vinch

Color Choices Cypher Camo Gray/Super Black

Scan with camera to view videos, key features and more.



TERYX® S LE





\$15,499



ICE GRAY/SUPER BLACK



METALLIC MATTE TWILIGHT BLUE/SUPER BLACK



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with (2) 36mm Mikuni throttle bodies

Ignition TCBI with Electronic Advance

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes **Ground Clearance** 12.2 in (max) / 11.2 in (std)

Fuel Capacity 7.9 gal

Turning Radius 17.7 ft

Cargo Bed **Dimensions (LxWxH)**

Cargo Bed Load Capacity

600 lb

Payload Capacity 1,100 lb

Seating Capacity 2

Towing Capacity 1,300 lb

Lighting (4) LED headlights, (2) incandescent taillights,

27.6 x 43.3 x 10.4 in

incandescent stoplight

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

DETAILS

Overall Height

Steel Tube Double-X Reinforcement Frame

Overall Length 118.1 in **Overall Width** 60.0 in

75.8 in **Curb Weight** 1,570.0 lb* / 1,572.2 lb* CA Model

Wheelbase

Instruments Multi-function digital meter with speedometer, fuel gauge,

> clock, hour meter, odometer, dual trip meter and parkingbrake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Wheel Type Alloy

Additional Features Roof

Color Choices Ice Gray/Super Black, Metallic Matte Twilight Blue/Super



