

Kawasaki

Let the Good Times Roll®



VERSYS

2025

Product Spec Book

2025

VERSYS® 1100 SE LT ABS

Kawasaki

Let the Good Times Roll®

MSRP

\$19,499

 METALLIC GRAPHITE GRAY/METALLIC DIABLO BLACK



POWER		Front Tire	120/70-17
Engine	4-stroke, in-line 4-cylinder, DOHC, liquid-cooled	Rear Tire	180/55-17
Displacement	1,099cc	Front Brakes	Dual 310mm petal discs with radial-mount 4-piston monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Bore x Stroke	77.0 x 59.0mm	Rear Brakes	Single 260mm petal disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)
Compression Ratio	11.8:1	DETAILS	
Maximum Horsepower	133.0 hp ¹ @ 9,000 rpm	Frame Type	Twin-tube, aluminum
Maximum Torque	82.5 lb-ft @ 7,600 rpm	Rake/Trail	27.0° / 4.0 in
Fuel System	DFI® with 38mm throttle bodies (4)	Overall Length	89.4 in
Ignition	TCBI with Electronic Advance	Overall Width	37.4 in
Transmission	6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch	Overall Height	60.2 in (windshield Hi) / 59.8 in (windshield Lo)
Final Drive	Chain	Ground Clearance	5.9 in
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Electronic Control Suspension (KECS), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness	Seat Height	33.1 in
PERFORMANCE		Estimated Dry Weight	520.4 lb** (+20 lb w/ saddlebags)
Front Suspension / Wheel Travel	43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/5.9 in	Curb Weight	571.1 lb* (+20 lb w/ saddlebags)
Rear Suspension / Wheel Travel	Horizontal back-link, Showa BFRC Lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.9 in	Fuel Capacity	5.5 gal
		Wheelbase	59.8 in
		Special Features	Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, USB Type-C outlet, Adjustable windshield, Grip heaters and hand guards, ERGO-FIT®, Highly Durable Paint, Smartphone Connectivity with Voice Command via RIDEOLGY THE APP MOTORCYCLE
		Color Choices	Metallic Graphite Gray/Metallic Diablo Black

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

VERSYS®-X 300 ABS

Kawasaki

Let the Good Times Roll®

MSRP

\$5,699

 CANDY LIME GREEN/METALLIC FLAT SPARK BLACK



POWER		Rear Tire	130/80-17
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Front Brakes	Single 290mm disc, ABS
Displacement	296cc	Rear Brakes	Single 220mm disc, ABS
Bore x Stroke	62.0 x 49.0mm	DETAILS	
Compression Ratio	10.6:1	Frame Type	Tubular, diamond
Maximum Torque	19.2 lb-ft @ 10,000 rpm	Rake/Trail	24.3° / 4.3 in
Fuel System	DFI® with 32mm throttle bodies (2)	Overall Length	85.4 in
Ignition	TCBI with Digital Advance	Overall Width	33.9 in
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Height	54.7 in
Final Drive	Chain	Ground Clearance	7.1 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Seat Height	32.1 in
PERFORMANCE		Estimated Dry Weight	350.6 lb**
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	Curb Weight	385.9 lb*
Rear Suspension / Wheel Travel	Uni-Trak® swingarm with 5-way spring preload adjustment/5.8 in	Fuel Capacity	4.5 gal
Front Tire	100/90-19	Wheelbase	57.1 in
		Special Features	ERGO-FIT®
		Color Choices	Candy Lime Green/Metallic Flat Spark Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.