

Kawasaki

Let the Good Times Roll®



VULCAN

Product Spec Book

2025

2025

VULCAN® 900 CLASSIC

Kawasaki

Let the Good Times Roll®



MSRP

\$9,399



METALLIC CARBON GRAY/PHANTOM BLUE



POWER		Front Tire	130/90-16
Engine	4-stroke, 55-degree V-twin, liquid-cooled	Rear Tire	180/70-15
Displacement	903cc	Front Brakes	Single 300mm hydraulic disc
Bore x Stroke	88.0 x 74.2mm	Rear Brakes	Single 270mm hydraulic disc
Compression Ratio	9.5:1	DETAILS	
Maximum Torque	58.2 lb-ft @ 3,500 rpm	Frame Type	Semi-double cradle, high-tensile steel
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves	Rake/Trail	32° /6.3 in
Ignition	TCBI with Electronic Advance	Overall Length	97.0 in
Transmission	5-speed with positive neutral finder	Overall Width	39.6 in
Final Drive	Kevlar-reinforced belt	Overall Height	41.9 in
PERFORMANCE		Ground Clearance	5.3 in
Front Suspension / Wheel Travel	41mm Showa telescopic fork/5.9 in	Seat Height	26.8 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	Curb Weight	619.6 lb*
		Fuel Capacity	5.3 gal
		Wheelbase	64.8 in
		Color Choices	Metallic Carbon Gray/Phantom Blue

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.

2025

VULCAN® 900 CLASSIC LT

Kawasaki

Let the Good Times Roll®



MSRP

\$10,399

METALLIC OCEAN BLUE/METALLIC MOONDUST GRAY



POWER		Front Tire	130/90-16
Engine	4-stroke, 55-degree V-twin, liquid-cooled	Rear Tire	180/70-15
Displacement	903cc	Front Brakes	Single 300mm hydraulic disc
Bore x Stroke	88.0 x 74.2mm	Rear Brakes	Single 270mm hydraulic disc
Compression Ratio	9.5:1	DETAILS	
Maximum Torque	58.2 lb-ft @ 3,500 rpm	Frame Type	Semi-double cradle, high-tensile steel
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves	Rake/Trail	32° /6.3 in
Ignition	TCBI with Electronic Advance	Overall Length	97.0 in
Transmission	5-speed with positive neutral finder	Overall Width	39.6 in
Final Drive	Kevlar-reinforced belt	Overall Height	58.3 in
PERFORMANCE		Ground Clearance	5.3 in
Front Suspension / Wheel Travel	41mm Showa telescopic fork/5.9 in	Seat Height	26.8 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	Curb Weight	657.1 lb*
		Fuel Capacity	5.3 gal
		Wheelbase	64.8 in
		Color Choices	Metallic Ocean Blue/Metallic Moondust Gray

2025

VULCAN® 900 CUSTOM

Kawasaki

Let the Good Times Roll®



MSRP

\$9,899



CANDY FIRE RED/EBONY



POWER

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

Front Tire	80/90-21
Rear Tire	180/70-15
Front Brakes	Single 300mm hydraulic disc
Rear Brakes	Single 270mm hydraulic disc

DETAILS

Frame Type	Semi-double cradle, high-tensile steel
Rake/Trail	33° / 7.2 in
Overall Length	94.7 in
Overall Width	35.2 in
Overall Height	44.1 in
Ground Clearance	5.5 in
Seat Height	27.0 in
Curb Weight	610.8 lb*
Fuel Capacity	5.3 gal
Wheelbase	64.8 in
Color Choices	Candy Fire Red/Ebony

PERFORMANCE

Front Suspension / Wheel Travel	41mm Showa telescopic fork/5.9 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.

2025

VULCAN® 1700 VAQUERO® ABS

Kawasaki

Let the Good Times Roll®



MSRP

\$19,499

METALLIC BRILLIANT GOLDEN BLACK

POWER		REAR TIRE	
Engine	4-stroke, 52-degree V-twin, liquid-cooled	Front Brakes	170/70-16
Displacement	1,700cc	Rear Brakes	Dual 300mm discs, dual four-piston calipers, K-ACT ABS
Bore x Stroke	102.0 x 104.0mm		Single 300mm disc, twin-piston caliper, K-ACT ABS
Compression Ratio	9.5:1	DETAILS	
Maximum Torque	107.6 lb-ft @ 2,750 rpm	Frame Type	Steel, double-cradle with box-section single-tube backbone
Fuel System	DFI® with 42mm throttle bodies (2)	Rake/Trail	30° / 7.0 in
Ignition	TCBI with Electronic Advance	Overall Length	98.8 in
Transmission	6-speed with overdrive and positive neutral finder	Overall Width	38.2 in
Final Drive	Carbon fiber-reinforced belt	Overall Height	50.8 in
Electronic Rider Aids	Electronic Cruise Control, Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS	Ground Clearance	5.7 in
PERFORMANCE		Seat Height	28.7 in
Front Suspension / Wheel Travel	45mm Showa telescopic fork/5.5 in	Curb Weight	844.5 lb*
Rear Suspension / Wheel Travel	Swingarm with twin air-assisted shocks, with 4-way adjustable rebound damping/3.1 in	Fuel Capacity	5.3 gal
Front Tire	130/90-16	Wheelbase	65.6 in
		Special Features	Integrated audio system with SiriusXM and intercom headset compatibility
		Color Choices	Metallic Brilliant Golden Black

2025

VULCAN® 1700 VOYAGER® ABS

Kawasaki

Let the Good Times Roll®



MSRP

\$20,199

METALLIC OCEAN BLUE/METALLIC MOONDUST GRAY



POWER		REAR	
Engine	4-stroke, 52-degree V-twin, liquid-cooled	Rear Tire	170/70-16
Displacement	1,700cc	Front Brakes	Dual 300mm discs, dual four-piston calipers, K-ACT ABS
Bore x Stroke	102.0 x 104.0mm	Rear Brakes	Single 300mm disc, twin-piston caliper, K-ACT ABS
Compression Ratio	9.5:1	DETAILS	
Maximum Torque	107.6 lb-ft @ 2,750 rpm	Frame Type	Steel, double-cradle with box-section single-tube backbone
Fuel System	DFI® with 42mm throttle bodies (2)	Rake/Trail	30° / 7.0 in
Ignition	TCBI with Electronic Advance	Overall Length	100.8 in
Transmission	6-speed with overdrive and positive neutral finder	Overall Width	39.2 in
Final Drive	Carbon fiber-reinforced belt	Overall Height	61.0 in
Electronic Rider Aids	Electronic Cruise Control, Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS	Ground Clearance	5.3 in
PERFORMANCE		Seat Height	28.7 in
Front Suspension / Wheel Travel	45mm Showa telescopic fork/5.5 in	Curb Weight	895.2 lb*
Rear Suspension / Wheel Travel	Swingarm with twin air-assisted shocks, with 4-way adjustable rebound damping/3.1 in	Fuel Capacity	5.3 gal
Front Tire	130/90-16	Wheelbase	65.6 in
		Special Features	Integrated audio system with SiriusXM and intercom headset compatibility
		Color Choices	Metallic Ocean Blue/Metallic Moondust Gray

2025

VULCAN® S

Kawasaki
Let the Good Times Roll®



MSRP NON-ABS
\$7,399

MSRP ABS
\$7,899

- METALLIC MATTE GRAPHITE GRAY/
METALLIC MATTE CARBON GRAY
- METALLIC FLAT SPARK BLACK



POWER	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Torque	46.3 lb-ft @ 6,600 rpm
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	6-speed with positive neutral finder
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)
PERFORMANCE	
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in

Front Tire	120/70-18
Rear Tire	160/60-17
Front Brakes	Single 300mm disc with twin-piston caliper (and ABS)
Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)
DETAILS	
Frame Type	High-tensile steel diamond frame
Rake/Trail	31° / 4.7 in
Overall Length	90.9 in
Overall Width	34.6 in
Overall Height	43.3 in
Ground Clearance	5.1 in
Seat Height	27.8 in
Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
Fuel Capacity	3.7 gal
Wheelbase	62.0 in
Special Features	ERGO-FIT®
Color Choices	Metallic Matte Graphite Gray/Metallic Matte Carbon Gray, Metallic Flat Spark Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

VULCAN® S CAFE ABS

Kawasaki

Let the Good Times Roll®



MSRP

\$8,499

 METALLIC MOONDUST GRAY/METALLIC SPARK BLACK



POWER	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Torque	46.3 lb-ft @ 6,600 rpm
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	6-speed with positive neutral finder
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)
PERFORMANCE	
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in

Front Tire	120/70-18
Rear Tire	160/60-17
Front Brakes	Single 300mm disc with twin-piston caliper, ABS
Rear Brakes	Single 250mm disc with single-piston caliper, ABS
DETAILS	
Frame Type	High-tensile steel diamond frame
Rake/Trail	31° / 4.7 in
Overall Length	90.9 in
Overall Width	34.6 in
Overall Height	44.5 in
Ground Clearance	5.1 in
Seat Height	27.8 in
Curb Weight	502.7 lb*
Fuel Capacity	3.7 gal
Wheelbase	62.0 in
Special Features	ERGO-FIT®
Color Choices	Metallic Moondust Gray/Metallic Spark Black

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.