

Kawasaki

Let the Good Times Roll®



W

2025

Product Spec Book

2025

W230 ABS



MSRP
\$5,599

 METALLIC OCEAN BLUE/EBONY

POWER

Engine	4-stroke, single-cylinder, SOHC, 2 valves, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.0:1
Maximum Torque	14.0 lb-ft @ 5,800 rpm
Fuel System	DFI® with 32mm throttle bodies
Ignition	TCBI with Digital Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/4.6 in
Rear Suspension / Wheel Travel	Twin shocks with spring preload adjustability/3.7 in

Front Tire	90/90-18
Rear Tire	110/90-17
Front Brakes	Single 265mm disc with 2-piston calipers, ABS
Rear Brakes	Single 220mm disc with 1-piston caliper, ABS

DETAILS

Frame Type	Semi-double cradle, steel
Rake/Trail	27.0° /3.7 in
Overall Length	83.6 in
Overall Width	31.4 in
Overall Height	42.9 in
Ground Clearance	5.9 in
Seat Height	29.3 in
Estimated Dry Weight	293.2 lb**
Curb Weight	315.2 lb*
Fuel Capacity	3.1 gal
Wheelbase	55.7 in
Color Choices	Metallic Ocean Blue/Ebony

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.

2025

W800 ABS



MSRP
\$10,399

 METALLIC BRILLIANT GOLDEN BLACK/EBONY



POWER		REAR SUSPENSION / WHEEL TRAVEL	
Engine	4-stroke, Parallel Twin, SOHC, 4 valves, air-cooled	Front Tire	Twin shocks with spring preload adjustability/4.2 in
Displacement	773cc	Rear Tire	100/90-19
Bore x Stroke	77.0 x 83.0mm	Front Brakes	130/80-18
Compression Ratio	8.4:1	Rear Brakes	Single 320mm disc with 2-piston calipers, ABS
Maximum Torque	46.4 lb-ft @ 4,800 rpm		Single 270mm disc with 2-piston caliper, ABS
Fuel System	DFI® with 34mm throttle bodies (2)	DETAILS	
Ignition	TCBI with Digital Advance	Frame Type	Double-cradle high tensile steel
Transmission	5-speed, return shift	Rake/Trail	26.0° / 3.7 in
Final Drive	Sealed chain	Overall Length	86.2 in
Electronic Rider Aids	Anti-lock Brake System	Overall Width	31.1 in
PERFORMANCE		Overall Height	42.3 in
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	Ground Clearance	4.9 in
		Seat Height	31.1 in
		Curb Weight	498.3 lb*
		Fuel Capacity	4.0 gal
		Wheelbase	57.7 in
		Color Choices	Metallic Brilliant Golden Black/Ebony

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.